

LF05CA -RGB3-P

Kod produktu: 55635



Dane techniczne:

- Construction wattage [PICOS] **72.00 W**
- Nominal voltage **24.00 V**
- Nominal current **3 A**
- Type of current **DC**
- Reverse Voltage **25 V**
- Input voltage range AC **23□25 V**
- Nominal wattage per meter **18.0 W**
- Rated wattage **39.00 W**
- Light color as per EN 12464-1 **Daylight**
- Luminous flux **1740 lm**
- Light color LED **RGB**
- Luminous flux per meter **435 lm**
- Beam angle **120 °**
- Length **4000.0 mm**
- Width **11.0 mm**
- Height **4.5 mm**
- Product weight **241.00 g**
- Cable length **500.0 mm**
- Length □ smallest unit **100.0 mm**
- Lifespan **50000 h**
- Dimmable **Yes**
- Standards **Acc. to EN 60598-1**
- Type of protection **IP67**
- Temperature range at storage **-40□85 °C**
- Temperature range in operation **-30□75 °C**
- Number of LEDs per module **200**
- Number of LEDs per meter **50**

Product benefits

- Uniform color changing
- Great design freedom thanks to flexibility and cuttability of module
- High-performance silicon for extremely long life and flexibility
- Simple connection thanks to premounted connectors
- Extraordinary design and high quality materials

- Toolless connection with the optional CONNECTsystem
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back

Areas of application

- Facade accent lighting
- Effect lighting in architecture
- Edge coupling
- Path lighting
- Suitable for outdoor use

Product features

- Flexible and splittable LED strip with inline multichip RGB LEDs
- Type of protection: IP67
- Dimmable
- Salt mist proof
- Highly UV-resistant

Equipment / Accessories

- Simplified connection with optional matching CONNECTsystem
- Quick installation with optional SLIM TRACK System
- Perfectly matched to OPTOTRONIC 24 V Electronic Control Gears



