

LF06A -W3F-865

Kod produktu: 55651



Dane techniczne:

- Construction wattage [PICOS] **48.00 W**
- Color temperature **6500 K**
- Light color as per EN 12464-1 **Daylight**
- Length **10000.0 mm**
- Dimmable **Yes**
- Energy efficiency class **A++**
- Color rendering index Ra > **80**
- Energy consumption **1 kWh/1000h**
- Nominal current **2 A**
- Height **2.1 mm**
- Product weight **132.00 g**
- Temperature range at storage **-40÷85 °C**
- Temperature range in operation **-30÷75 °C**
- Luminous flux **4230 lm**
- Reverse Voltage **25 V**
- Input voltage range AC **23÷25 V**
- Light color LED **White**
- Luminous efficacy **88 lm/W**
- Number of LEDs per module **600**
- Number of LEDs per meter **60**
- Nominal wattage per meter **4.8 W**
- Luminous flux per meter **425 lm**
- Nominal voltage **24.00 V**
- Type of current **DC**
- Beam angle **120 °**
- Width **8.0 mm**
- Length □ smallest unit **100.0 mm**
- Lifespan **50000 h**

Product benefits

- Very long for seamless bands of light
- Large selection of light colors
- Great design freedom thanks to flexibility and cuttability of module
- Simple mounting and connection

- Toolless connection with the optional CONNECTsystem
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back

Areas of application

- Cove lighting
- Signage
- Advertising and lettering

Product features

- Flexible and cuttable LED strip
- Luminous flux: up to 425 lm/m
- Module efficacy: up to 88 lm/W
- Dimmable
- Fine White (3 SDCM)

Equipment / Accessories

- Simplified connection with optional matching CONNECTsystem
- Quick installation with optional SLIM TRACK System
- Perfectly matched to OPTOTRONIC 24 V Electronic Control Gears



