

HALOLINE 1500 W 230 V R7S

Kod produktu: 55718



Dane techniczne:

- Construction wattage [PICOS] **1500.00 W**
- Claimed equiv. conventional lamp power **1500 W**
- Nominal wattage **1500.00 W**
- Nominal luminous flux **33000 lm**
- Rated luminous flux **33000 lm**
- Overall length **250.7 mm**
- Length **256.1 mm**
- Base (standard designation) **R7s**
- Order reference **64760 1500W 230**
- Energy consumption **1500 kWh/1000h**
- ILCOS **HDG-1500-230-R7s-256,1**
- Fuse, quick-acting **10.0 A**
- Nominal voltage **230 V**
- Power factor λ **1.00**
- Color temperature **2900 K**
- Light color as per EN 12464-1 **Warm White**
- Color rendering index Ra **100**
- Starting time **0.0 s**
- Warm-up time (60 %) **0.00 s**
- Diameter **12.0 mm**
- Outer bulb **T12**
- Nominal lamp life time **2000 h**
- Rated lamp life time **2000 h**
- Number of switching cycles **50000**
- Lumen main.fact.at end of nom.life time **0.80**
- Mercury-free **Yes**
- Lamp mercury content **0.0 mg**
- Product remark **Fuse protection with indicated values recommended acc. to IEC60357, EN60357/For outdoor applications and operation in damp locations special approved fixtures are required**
- Dimmable **Yes**
- Burning position **p15**
- Non-standard conditions **P 15**
- Energy efficiency class **C**

Product benefits

- Brilliant accent light
- No transformer required
- Contains no mercury

Areas of application

- Ideal for emphasizing and accentuating buildings
- General illumination
- Entrance lighting
- Pathway lighting
- Garden lighting
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications

Product features

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index Ra: 100
- Color temperature: 3,000 K
- Burning position: p15



