

HALOSPOT 70 20 W 12 V 24° BA15D

Kod produktu: 55736



Dane techniczne:

- Construction wattage [PICOS] **20.00 W**
- Nominal wattage **20.00 W**
- Rated useful luminous flux 90° **150 lm**
- Beam angle **24 °**
- Nominal lamp life time **3000 h**
- Rated lamp life time **3000 h**
- Energy efficiency class **C**
- Order reference **41970 FL 20W 12**
- Luminous intensity **900 cd**
- Nominal useful luminous flux 90° **150 lm**
- Energy consumption **22 kWh/1000h**
- ILCOS **HMGS//UB-20-12-BA15D-70/24**
- Nominal voltage **12 V**
- Power factor λ **1.00**
- Color temperature **3000 K**
- Light color as per EN 12464-1 **Warm White**
- Color rendering index Ra **100**
- Starting time **0.0 s**
- Warm-up time (60 %) **0.00 s**
- Overall length **45.6 mm**
- Diameter **70.5 mm**
- Length **50.0 mm**
- Outer bulb **AR70**
- Maximum diameter **71.0 mm**
- Number of switching cycles **75000**
- Lumen main.fact.at end of nom.life time **0.75**
- Base (standard designation) **BA15d**
- Mercury-free **Yes**
- Lamp mercury content **0.0 mg**
- Dimmable **Yes**
- Burning position **Any**

Product benefits

- Brilliant accent light

- Cap for reduced glare and ease of handling
- Excellent distribution of light thanks to faceted reflector
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Drastically reduced thermal load in fixture thanks to aluminum-coated reflector
- Contains no mercury

Areas of application

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

Product features

- Average life: 3,000 h
- Dimmable
- Color rendering index Ra: 100
- Color temperature: 3,000 K



