

DULUX D 10 W/830

Kod produktu: 55949



Dane techniczne:

- Construction wattage [PICOS] **10.00 W**
- Nominal wattage **10.00 W**
- Operating frequency **50 Hz**
- Color temperature **3000 K**
- Nominal luminous flux **600 lm**
- Rated luminous flux **600 lm**
- Light color as per EN 12464-1 **LUMILUX Warm White**
- Overall length **108.0 mm**
- Length **110.0 mm**
- Base (standard designation) **G24d-1**
- Color rendering index Ra **80**89
- Energy consumption **13 kWh/1000h**
- ILCOS **FSQ-10/830-I-G24d-1**
- Product weight **33.00 g**
- Light color **830**
- Luminous flux at 25 °C **600 lm**
- Length acc. to IEC standard **95 mm**
- Luminance **4 cd/cm²**
- Length with base excl. base pins/connection **87.00 mm**
- Color rendering group **1B**
- Rated LLMF at 4,000 h **0.78**
- Rated LLMF at 6,000 h **0.76**
- Rated LLMF at 8,000 h **0.75**
- Tube diameter **12 mm**
- Nominal lamp life time **10000 h**
- Rated lamp life time **10000 h**
- Lifespan **10000 h**
- Rated lamp survival factor at 2,000 h **0.98**
- Rated lamp survival factor at 4,000 h **0.98**
- Rated lamp survival factor at 6,000 h **0.95**
- Service life **6500 h**
- Operation mode LLMF/LSF **50 Hz**
- Rated lamp survival factor at 8,000 h **0.81**
- Appropriate disposal acc. to WEEE **Yes**
- Lamp mercury content **1.4 mg**

- Suitable for indoor **Yes**
- Energy efficiency class **A**
- Rated ambient temp.w.max.luminous flux **25.0 °C**

Product benefits

- Extremely economical
- Good quality of light
- Excellent luminous flux
- Long service life
- Improved maintenance

Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product features

- Average life: 10,000 h
- Color rendering index Ra: 80...89
- Short and compact pin-base lamp with double-turn tubes
- Single-ended two-pin plug-in G24d base

Equipment / Accessories

- Suitable for operation on conventional control gear

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp





