

DULUX L SP 24 W/830 2G11

Kod produktu: 55988



Dane techniczne:

- Construction wattage [PICOS] **24.00 W**
- Nominal wattage **24.00 W**
- Rated wattage **18.00 W**
- Color temperature **3000 K**
- Nominal luminous flux **1675 lm**
- Rated luminous flux **1675 lm**
- Light color as per EN 12464-1 **LUMILUX Warm White**
- Color rendering index Ra **80**89
- Light color **830**
- Luminous flux at 25 °C **1800 lm**
- Rated LLMF at 4,000 h **0.90**
- Rated LLMF at 6,000 h **0.88**
- Rated LLMF at 8,000 h **0.86**
- Rated LLMF at 12,000 h **0.84**
- Luminance **2.1 cd/cm²**
- Rated LLMF at 16,000 h **0.81**
- Rated LLMF at 20,000 h **0.80**
- Overall length **309.0 mm**
- Length **309.0 mm**
- Product weight **75.00 g**
- Tube diameter **17.5 mm**
- Length with base excl. base pins/connection **309.00 mm**
- Nominal lamp life time **20000 h**
- Rated lamp life time **20000 h**
- Lifespan **20000 h**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.99**
- Rated lamp survival factor at 6,000 h **0.99**
- Service life **13000 h**
- Operation mode LLMF/LSF **HF**
- Rated lamp survival factor at 8,000 h **0.99**
- Rated lamp survival factor at 12,000 h **0.95**
- Rated lamp survival factor at 16,000 h **0.81**
- Rated lamp survival factor at 20,000 h **0.50**
- Base (standard designation) **2G11**

- Appropriate disposal acc. to WEEE **Yes**
- Lamp mercury content **1.7 mg**
- Suitable for indoor **Yes**
- Energy efficiency class **A**
- Energy consumption **27 kWh/1000h**
- ILCOS **FSD//L-24/830-E-2G11-43,9/309**
- Rated ambient temp.w.max.luminous flux **5.0 °C**

Product benefits

- Very economical
- Optimum luminous flux at low ambient temperatures (+5 °C)
- Good quality of light
- Long service life

Areas of application

- Street and city lighting
- Industry
- Applications with special thermal requirements

Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in 2G11 base
- Average life: 20,000 h (with QUICKTRONIC)
- Color rendering index Ra: 80...89

Equipment / Accessories

- Suitable for operation on electronic and conventional control gear

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp





