

# DULUX L 24 W/840 2G11

Kod produktu: 55991



## Dane techniczne:

- Construction wattage [PICOS] **24.00 W**
- Nominal wattage **24.00 W**
- Color temperature **4000 K**
- Nominal luminous flux **1800 lm**
- Rated luminous flux **1800 lm**
- Light color as per EN 12464-1 **LUMILUX Cool White**
- Overall length
- Light color **840**
- Color rendering group **1B**
- Luminous flux at 25 °C **1800 lm**
- Rated LLMF at 4,000 h **0.90**
- Rated LLMF at 6,000 h **0.88**
- Rated LLMF at 8,000 h **0.86**
- Rated LLMF at 12,000 h **0.84**
- Luminance **2.1 cd/cm<sup>2</sup>**
- Rated LLMF at 16,000 h **0.81**
- Rated LLMF at 20,000 h **0.80**
- Color rendering index Ra **80-89**

## Product benefits

- Very economical
- Outstanding luminous flux
- Outstanding luminous efficiency
- Long service life
- OSRAM System+ Guarantee in combination with OSRAM QUICKTRONIC ECG
- Less than half as long as tubular fluorescent lamps
- Improved maintenance

## Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

- Industry

#### **Product features**

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in 2G11 base
- Dimmable (1...100 % with QUICKTRONIC QT<sub>i</sub> DALI/DIM)
- Color rendering index Ra: 80...89
- Average life: 20,000 h (with QUICKTRONIC)
- Operates on battery, solar and AC power with suitable electronic control gear
- Also available in blue

#### **Equipment / Accessories**

- Suitable for standard control gears and starters
- Suitable for operation on electronic and conventional control gear