

DULUX L 36 W/930 2G11

Kod produktu: 56005



Dane techniczne:

- Construction wattage [PICOS] **36.00 W**
- Nominal wattage **36.00 W**
- Color temperature **3000 K**
- Nominal luminous flux **2350 lm**
- Rated luminous flux **2350 lm**
- Light color as per EN 12464-1 **LUMILUX DE LUXE Warm White**
- Overall length **411.0 mm**
- Length **411.0 mm**
- Nominal lamp life time **20000 h**
- Rated lamp life time **20000 h**
- Energy efficiency class **A**
- Lamp mercury content **1.7 mg**
- Energy consumption **40 kWh/1000h**
- ILCOS **FSD-36/930-E-2G11-43,9/411**
- Product weight **94.00 g**
- Product remark **For ECG and CCG operation**
- Light color **930**
- Luminous flux at 25 °C **2350 lm**
- Rated LLMF at 4,000 h **0.85**
- Rated LLMF at 6,000 h **0.83**
- Rated LLMF at 8,000 h **0.81**
- Service life **13000 h**
- Rated LLMF at 12,000 h **0.79**
- Luminance **2.8 cd/cm²**
- Length with base excl. base pins/connection **411.00 mm**
- Rated LLMF at 16,000 h **0.78**
- Rated LLMF at 20,000 h **0.76**
- Color rendering index $R_a \geq 90$
- Tube diameter **17.5 mm**
- Lifespan **20000 h**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.99**
- Rated lamp survival factor at 6,000 h **0.99**
- Operation mode LLMF/LSF **HF**
- Rated lamp survival factor at 8,000 h **0.99**

- Rated lamp survival factor at 12,000 h **0.95**
- Rated lamp survival factor at 16,000 h **0.81**
- Rated lamp survival factor at 20,000 h **0.50**
- Base (standard designation) **2G11**
- Appropriate disposal acc. to WEEE **Yes**
- Suitable for indoor **Yes**
- Rated ambient temp.w.max.luminous flux **25.0 °C**

Product benefits

- Very economical and efficient
- Good quality of light
- Outstanding luminous efficiency
- Long service life
- Improved maintenance

Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in 2G11 base
- Color rendering index Ra: ≥ 90
- Average life: 20,000 h (with QUICKTRONIC)

Equipment / Accessories

- Suitable for operation on electronic and conventional control gear

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp



