

DULUX L 40 W/865 2G11

Kod produktu: 56010



Dane techniczne:

- Construction wattage [PICOS] **40.00 W**
- Nominal wattage **40.00 W**
- Color temperature **6500 K**
- Nominal luminous flux **3325 lm**
- Rated luminous flux **3200 lm**
- Light color as per EN 12464-1 **LUMILUX Cool Daylight**
- Overall length **533.0 mm**
- Length **533.0 mm**
- Nominal lamp life time **20000 h**
- Rated lamp life time **20000 h**
- Base (standard designation) **2G11**
- Appropriate disposal acc. to WEEE **Yes**
- Energy efficiency class **A**
- Lamp mercury content **1.7 mg**
- Energy consumption **44 kWh/1000h**
- ILCOS **FSDH-40/865-/P/-2G11-43,9/533**
- Product weight **115.00 g**
- Tube diameter **17.5 mm**
- Lifespan **20000 h**
- Product remark **For ECG operation only**
- Light color **865**
- Luminous flux at 25 °C **3325 lm**
- Rated LLMF at 4,000 h **0.81**
- Rated LLMF at 6,000 h **0.79**
- Rated LLMF at 8,000 h **0.77**
- Length acc. to IEC standard **535 mm**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.99**
- Rated lamp survival factor at 6,000 h **0.99**
- Service life **13000 h**
- Operation mode LLMF/LSF **HF**
- Rated lamp survival factor at 8,000 h **0.99**
- Suitable for indoor **Yes**
- Rated LLMF at 12,000 h **0.76**
- Rated lamp survival factor at 12,000 h **0.95**

- Luminance **2.3 cd/cm²**
- Length with base excl. base pins/connection **533.00 mm**
- Rated ambient temp.w.max.luminous flux **25.0 °C**
- Rated LLMF at 16,000 h **0.73**
- Rated LLMF at 20,000 h **0.72**
- Rated lamp survival factor at 16,000 h **0.81**
- Rated lamp survival factor at 20,000 h **0.50**
- Color rendering index Ra **80-89**

Product benefits

- Very economical
- Outstanding luminous flux
- Outstanding luminous efficiency
- Long service life
- OSRAM System+ Guarantee in combination with OSRAM QUICKTRONIC ECG
- Less than half as long as tubular fluorescent lamps
- Improved maintenance

Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in 2G11 base
- Dimmable (1...100 % with QUICKTRONIC QT_i DALI/DIM)
- Color rendering index Ra: 80...89
- Average life: 20,000 h (with QUICKTRONIC)
- Operates on battery, solar and AC power with suitable electronic control gear
- Also available in blue

Equipment / Accessories

- Suitable for standard control gears and starters
- Suitable for operation on electronic and conventional control gear



