

DULUX T PLUS 26 W/840

Kod produktu: 56052



Dane techniczne:

- Construction wattage [PICOS] **26.50 W**
- Nominal wattage **26.50 W**
- Color temperature **4000 K**
- Nominal luminous flux **1800 lm**
- Rated luminous flux **1800 lm**
- Light color as per EN 12464-1 **LUMILUX Cool White**
- Overall length **139.0 mm**
- Length **139.0 mm**
- Base (standard designation) **GX24d-3**
- Energy efficiency class **B**
- Lamp mercury content **1.9 mg**
- Energy consumption **32 kWh/1000h**
- ILCOS **FSM-26/840-I-G2X4d-3**
- Product weight **63.00 g**
- Light color **840**
- Luminous flux at 25 °C **1800 lm**
- Rated LLMF at 4,000 h **0.80**
- Rated LLMF at 6,000 h **0.77**
- Length acc. to IEC standard **130 mm**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.99**
- Service life **6500 h**
- Luminance **6 cd/cm²**
- Length with base excl. base pins/connection **116.00 mm**
- Color rendering index Ra **80□89**
- Color rendering group **1B**
- Rated LLMF at 8,000 h **0.75**
- Tube diameter **12 mm**
- Nominal lamp life time **10000 h**
- Rated lamp life time **10000 h**
- Lifespan **10000 h**
- Rated lamp survival factor at 6,000 h **0.95**
- Operation mode LLMF/LSF **50 Hz**
- Rated lamp survival factor at 8,000 h **0.81**
- Appropriate disposal acc. to WEEE **Yes**

- Suitable for indoor **Yes**
- Rated ambient temp.w.max.luminous flux **25.0 °C**

Product benefits

- Very economical
- Good quality of light
- Excellent luminous flux
- Long service life
- Improved maintenance

Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industrial lighting

Product features

- Average life: 10,000 h
- Color rendering index Ra: 80...89
- Short and compact pin-base lamp with triple-turn tubes
- Single-ended two-pin plug-in GX24d base

Equipment / Accessories

- Suitable for operation on conventional control gear
- Suitable for 0.22 A control gear only (DULUX T 18 W PLUS)

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp





