

DULUX T/E CONSTANT 42 W/840

Kod produktu: 56074



Dane techniczne:

- Construction wattage [PICOS] **43.00 W**
- Nominal wattage **43.00 W**
- Color temperature **4000 K**
- Nominal luminous flux **3200 lm**
- Rated luminous flux **3200 lm**
- Light color as per EN 12464-1 **LUMILUX Cool White**
- Overall length **165.0 mm**
- Length **165.0 mm**
- Base (standard designation) **GX24q-4**
- Dimmable **Yes**
- Color rendering index Ra **80**
- Lamp mercury content **2.6 mg**
- Energy consumption **51 kWh/1000h**
- ILCOS **FSMH//L//H-42/840-P/-GX24q-4**
- Product weight **76.00 g**
- Product remark **For ECG operation only**
- Light color **840**
- Luminous flux at 25 °C **3200 lm**
- Length acc. to IEC standard **155 mm**
- Luminance **7 cd/cm²**
- Length with base excl. base pins/connection **149.00 mm**
- Rated lamp efficacy (HF data 25 °C) **Under clarification by authority and standardization body**
- Color rendering group **1B**
- Rated LLMF at 4,000 h **0.86**
- Rated LLMF at 6,000 h **0.84**
- Rated LLMF at 8,000 h **0.82**
- Rated LLMF at 12,000 h **0.79**
- Rated LLMF at 16,000 h **0.78**
- Rated LLMF at 20,000 h **0.76**
- Tube diameter **12 mm**
- Nominal lamp life time **20000 h**
- Rated lamp life time **20000 h**
- Lifespan **20000 h**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.99**

- Rated lamp survival factor at 6,000 h **0.99**
- Service life **13000 h**
- Operation mode LLMF/LSF **HF**
- Rated lamp survival factor at 8,000 h **0.99**
- Rated lamp survival factor at 12,000 h **0.95**
- Rated lamp survival factor at 16,000 h **0.81**
- Rated lamp survival factor at 20,000 h **0.50**
- Appropriate disposal acc. to WEEE **Yes**
- Suitable for indoor **Yes**
- Energy efficiency class **A**
- Rated ambient temp.w.max.luminous flux **25.0 °C**

Product benefits

- Very economical
- Excellent luminous flux at high and low ambient temperatures
- Good quality of light
- Long service life
- Improved maintenance

Areas of application

- Street and city lighting
- Industrial lighting
- Hot luminaires
- Locations with special thermal requirements
- Outdoor applications only in suitable luminaires

Product features

- Average life: 20,000 h (with QUICKTRONIC)
- Color rendering index Ra: 80...89
- Luminous flux >90 % in a temperature range from +10...+70 °C
- Dimmable (3...100 %)
- Short and compact pin-base lamp with triple-turn tubes
- Single-ended four-pin plug-in GX24q base with shortened base casing

Equipment / Accessories

- Suitable for operation on electronic control gear

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp





