

HO 24 W/830

Kod produktu: 56103



Dane techniczne:

- Color rendering index Ra ≥ 80
- Rated LLMF at 4,000 h **0.92**
- Rated LLMF at 6,000 h **0.91**
- Rated LLMF at 8,000 h **0.90**
- Rated LLMF at 12,000 h **0.90**
- Rated LLMF at 20,000 h **0.89**
- Rated LLMF at 2,000 h **0.95**
- Diameter **16.0 mm**
- Tube diameter **16 mm**
- Lifespan **24000 h**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.99**
- Rated lamp survival factor at 6,000 h **0.99**
- Service life **19000 h**
- Operation mode LLMF/LSF **HF**
- Rated lamp survival factor at 8,000 h **0.99**
- Rated lamp survival factor at 12,000 h **0.99**
- Rated ambient temp.w.max.luminous flux **35.0 °C**

Product benefits

- Excellent luminous flux
- Up to 20 % more economical than LUMILUX T8
- Up to 50 % smaller volume than comparable T8 lamps
- Natural colors

Areas of application

- Industry
- Public buildings
- Offices
- Tunnels, underpasses
- Car parks

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Long average lifetime: up to 24,000 h (with QUICKTRONIC ECG)
- Good color rendering group: 1B (Ra: 80...89)
- Dimmable

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp

System guarantee

OSRAM System+ Guarantee in combination with OSRAM ECGs