

# HO 39 W/827

Kod produktu: 56110



## Dane techniczne:

- Construction wattage [PICOS] **38.00 W**
- Nominal wattage **38.00 W**
- Color temperature **2700 K**
- Nominal luminous flux **3100 lm**
- Rated luminous flux **3100 lm**
- Light color as per EN 12464-1 **LUMILUX INTERNA**
- Length **849.0 mm**
- Nominal lamp life time **16000 h**
- Rated lamp life time **16000 h**
- Maximum diameter **16.0 mm**
- Light color **827**
- Luminous flux at 25 °C **3100 lm**
- Length with base excl. base pins/connection **849.00 mm**
- Rated lamp efficacy (HF data 25 °C) **Under clarification by authority and standardization body**
- Rated LLMF at 16,000 h **0.90**
- Rated lamp survival factor at 16,000 h **0.97**
- Rated lamp survival factor at 20,000 h **0.85**
- Luminous flux at 35 °C **3500 lm**
- Rated lamp efficacy (standard condition) **82 lm/W**
- Color rendering index Ra **≥80**
- Rated LLMF at 4,000 h **0.92**
- Rated LLMF at 6,000 h **0.91**
- Rated LLMF at 8,000 h **0.90**
- Rated LLMF at 12,000 h **0.90**
- Rated LLMF at 20,000 h **0.89**
- Rated LLMF at 2,000 h **0.95**
- Diameter **16.0 mm**
- Tube diameter **16 mm**
- Lifespan **24000 h**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.99**
- Rated lamp survival factor at 6,000 h **0.99**
- Service life **19000 h**
- Operation mode LLMF/LSF **HF**
- Rated lamp survival factor at 8,000 h **0.99**

- Rated lamp survival factor at 12,000 h **0.99**
- Rated ambient temp.w.max.luminous flux **35.0 °C**

#### **Product benefits**

- Excellent luminous flux
- Up to 20 % more economical than LUMILUX T8
- Up to 50 % smaller volume than comparable T8 lamps
- Natural colors

#### **Areas of application**

- Industry
- Public buildings
- Offices
- Tunnels, underpasses
- Car parks

#### **Product features**

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Long average lifetime: up to 24,000 h (with QUICKTRONIC ECG)
- Good color rendering group: 1B (Ra: 80...89)
- Dimmable

#### **Safety advice**

In case of lamp breakage: [www.osram.com/brokenlamp](http://www.osram.com/brokenlamp)

#### **System guarantee**

OSRAM System+ Guarantee in combination with OSRAM ECGs