

L 22 W/865 G10Q

Kod produktu: 56231



Dane techniczne:

- Construction wattage [PICOS] **22.00 W**
- Nominal voltage **62 V**
- Nominal wattage **22.00 W**
- Color temperature **6500 K**
- Nominal luminous flux **1300 lm**
- Rated luminous flux **1300 lm**
- Light color as per EN 12464-1 **LUMILUX Cool White**
- Diameter **216.0 mm**
- Length **216.0 mm**
- Energy efficiency class **B**
- Lamp mercury content **9.0 mg**
- Energy consumption **27 kWh/1000h**
- Lifespan **7500 h**
- Light color **865**
- Luminous flux at 25 °C **1300 lm**
- Rated LLMF at 4,000 h **0.74**
- Rated LLMF at 6,000 h **0.72**
- Rated LLMF at 8,000 h **0.70**
- Rated lamp survival factor at 2,000 h **0.99**
- Service life **6000 h**
- Rated lamp efficacy (standard condition) **59 lm/W**
- Rated LLMF at 2,000 h **0.80**
- Color rendering index Ra **80±89**
- Tube diameter **29 mm**
- Nominal lamp life time **9000 h**
- Rated lamp life time **9000 h**
- Rated lamp survival factor at 4,000 h **0.95**
- Rated lamp survival factor at 6,000 h **0.83**
- Operation mode LLMF/LSF **50 Hz**
- Rated lamp survival factor at 8,000 h **0.62**
- Base (standard designation) **G10q**
- Appropriate disposal acc. to WEEE **Yes**
- Suitable for indoor **Yes**
- Rated ambient temp.w.max.luminous flux **25.0 °C**

Product benefits

- Extremely economical
- Good quality of light
- Excellent luminous flux
- Excellent uniform illumination with no shadows

Areas of application

- Public buildings
- Restaurants
- Industry
- Shops
- Supermarkets and department stores
- Hotels

Product features

- Good color rendering group: 1B (Ra: 80...89)
- Good average lifetime
- Single-ended round fluorescent lamp
- Dimmable

Equipment / Accessories

- Suitable for operation on electronic and conventional control gears

Safety advice

In case of lamp breakage: www.osram.com/brokenlamp



