

# L 58 W/827

Kod produktu: 56287



## Dane techniczne:

- Rated lamp efficacy (HF data 25 °C) **Under clarification by authority and standardization body**
- Color rendering index Ra **≥80**
- Diameter **26.0 mm**
- Tube diameter **26 mm**
- Lifespan **20000 h**
- Operation mode LLMF/LSF **50 Hz**
- Base (standard designation) **G13**
- Appropriate disposal acc. to WEEE **Yes**
- Suitable for indoor **Yes**
- Rated ambient temp.w.max.luminous flux **25.0 °C**

## Product benefits

- Proven lamp technology
- Good economy thanks to high efficiency
- Available in many different light colors (2,700...8,000 K) for various applications

## Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

## Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering group: 1B (Ra: 80...89)
- Dimmable
- Top-quality three-band phosphor: LUMILUX

## Safety advice

In case of lamp breakage: [www.osram.com/brokenlamp](http://www.osram.com/brokenlamp)

**System guarantee**

OSRAM System+ Guarantee in combination with OSRAM ECGs