

L 70 W/840

Kod produktu: 56308



Dane techniczne:

- Construction wattage [PICOS] **69.50 W**
- Nominal voltage **129 V**
- Nominal wattage **70.00 W**
- Color temperature **4000 K**
- Nominal luminous flux **6000 lm**
- Rated luminous flux **6000 lm**
- Light color as per EN 12464-1 **LUMILUX Cool White**
- Length **1778.0 mm**
- Nominal lamp life time **15000 h**
- Rated lamp life time **15000 h**
- Dimmable **Yes**
- Energy efficiency class **A**
- Lamp mercury content **3.1 mg**
- Energy consumption **70 kWh/1000h**
- Light color **840**
- Luminous flux at 25 °C **6200 lm**
- Rated LLMF at 4,000 h **0.95**
- Rated LLMF at 6,000 h **0.94**
- Rated LLMF at 8,000 h **0.92**
- Rated lamp survival factor at 2,000 h **1.00**
- Rated lamp survival factor at 4,000 h **1.00**
- Rated lamp survival factor at 6,000 h **1.00**
- Service life **18000 h**
- Rated lamp survival factor at 8,000 h **1.00**
- Rated LLMF at 12,000 h **0.91**
- Rated lamp survival factor at 12,000 h **0.99**
- Length with base excl. base pins/connection **1764.00 mm**
- Rated LLMF at 16,000 h **0.90**
- Rated LLMF at 20,000 h **0.89**
- Rated lamp survival factor at 16,000 h **0.90**
- Rated lamp survival factor at 20,000 h **0.50**
- Rated LLMF at 2,000 h **0.96**
- Color coordinates chromaticity diagram **0.38/0.38**
- Lamp current **0.47000 A**
- Rated lamp efficacy (HF data 25 °C) **Under clarification by authority and standardization body**

- Color rendering index Ra ≥ 80
- Diameter **26.0 mm**
- Tube diameter **26 mm**
- Lifespan **20000 h**
- Operation mode LLMF/LSF **50 Hz**
- Base (standard designation) **G13**
- Appropriate disposal acc. to WEEE **Yes**
- Suitable for indoor **Yes**
- Rated ambient temp.w.max.luminous flux **25.0 °C**

Product benefits

- Proven lamp technology
- Good economy thanks to high efficiency
- Available in many different light colors (2,700...8,000 K) for various applications

Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

Product features


- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering group: 1B (Ra: 80...89)
- Dimmable
- Top-quality three-band phosphor: LUMILUX


Safety advice

In case of lamp breakage: www.osram.com/brokenlamp

System guarantee

OSRAM System+ Guarantee in combination with OSRAM ECGs





G13
IEC 7004-51
DIN 49653 T1

