

NAV-T 1000 W E40

Kod produktu: 56400



Dane techniczne:

- Construction wattage [PICOS] **960.00 W**
- Nominal voltage **110 V**
- Nominal wattage **1000.00 W**
- Rated lamp efficacy (standard condition) **135 lm/W**
- Lamp current **10.60000 A**
- Ignition voltage **3.6 / 5.0 kVp**
- Color temperature **2000 K**
- Rated luminous flux **130000 lm**
- Color rendering index $R_a \leq 25$
- Rated LLMF at 4,000 h **0.93**
- Rated LLMF at 6,000 h **0.91**
- Rated LLMF at 8,000 h **0.89**
- Rated LLMF at 12,000 h **0.84**
- Rated LLMF at 16,000 h **0.81**
- Rated LLMF at 20,000 h **0.79**
- Rated LLMF at 2,000 h **0.96**
- Diameter **66.0 mm**
- Length **360.0 mm**
- Product weight **300.00 g**
- Light center length (LCL) **240.0 mm**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.98**
- Rated lamp survival factor at 8,000 h **0.95**
- Rated lamp survival factor at 12,000 h **0.87**
- Rated lamp survival factor at 16,000 h **0.74**
- Rated lamp survival factor at 20,000 h **0.50**
- Lifespan B50 **20000 h**
- Lifespan B10 **11000 h**
- Lifespan B5 **8000 h**
- Base (standard designation) **E40**
- Lamp mercury content **39.0 mg**
- Design / version **Clear**
- Dimmable **Yes**
- Burning position **Any**
- Enclosed luminaire required **No**

- Energy efficiency class **A++**
- Energy consumption **1056 kWh/1000h**
- ILCOS **ST-1000-H/E/SL-E40-66/360**
- Maximum permitted outer bulb temperature **400 °C**
- Maximum permitted base edge temperature **250 °C**

Product benefits

- High luminous efficacy

Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product features

- Service lifetime: 3 years (at approx. 11 h/day)
- Average lifetime: up to 20,000 hours
- ErP compliant according to EU Directive 245/2009

