

OT 60/220...240/12 P

Kod produktu: 56420



Dane techniczne:

- Nominal voltage **220□240 V**
- Power factor λ **0.98/0.93**
- Length **180.0 mm**
- Dimmable **Yes**
- Nominal output power **60 W**
- Input voltage AC **198□264 V**
- Device power loss **9.0 W**
- ECG efficiency **86 %**
- Nominal current **0.33 A**
- Inrush current **35 A**
- Max. no. of ECGs on circuit breaker 10 A **11**
- Max. no. of ECGs on circuit breaker 16 A **17**
- Surge capability (L-N) **3 kV**
- Width **50.0 mm**
- Height **34.0 mm**
- Mounting hole spacing, length **171.0 mm**
- Mounting hole spacing, width **14.0 mm**
- Cable cross-section, input side **1.0 mm²**
- Product weight **700.00 g**
- Cable cross-section, output side **1.0 mm²**
- Casing material **Metal**
- Max.housing temperature in case of fault **100 °C**
- Suitable for fixtures with prot. class **II**
- Approval marks □ approval **CE / ENEC 18 / CB / C-Tick**
- Standards **acc. to IEC 61347-1/acc. to IEC 61347-2-13/acc. to IEC 62384/acc. to CISPR 15/acc. to IEC 61000-3-2/acc. to IEC 61000-3-3/acc. to IEC 61547**
- Type of protection **IP67**
- Mains frequency **50□60 Hz**
- Nominal output voltage **12.5 V**
- Galvanic isolation primary/secondary **3.75 kV**
- Wire preparation length, input side **10 mm**
- ECG lifetime **50000 h**
- Overheating protection **Automatic reversible**
- Max. cable length to lamp/LED module **10 m**
- No-load proof **Yes**

- Overload protection **Automatic reversible**
- Short-circuit protection **Automatic reversible**
- Ambient temperature range **-25 $\square$ +55 °C**
- Maximum temperature at test point **80 °C**
- Temperature range at storage **-40 $\square$ 85 °C**

Product benefits

- Versatile scope of application due to output power range of up to 120 W
- Very high efficiency and reliability
- High IP protection (up to IP67)
- High surge protection: up to 3 kV (L-N) / 6 kV (L/N-PE)

Areas of application

- Suitable for indoor and outdoor installations
- Ideal for mounting in very tight spaces

