

OTi DALI DIM

Kod produktu: 56436



Dane techniczne:

- Nominal voltage **100-24 V**
- Nominal output power **120 W**
- Input voltage AC **10.5-24 V**
- Mains frequency **0 Hz**
- Nominal output voltage **10.5-24 V**
- Device power loss **2.6 W**
- ECG efficiency **97 %**
- Galvanic isolation primary/secondary **3.75 kV**
- Length **172.0 mm**
- Width **42.0 mm**
- Height **20.0 mm**
- Mounting hole spacing, length **164.0 mm**
- Cable cross-section, input side **0.5-1.5 mm²**
- Product weight **75.00 g**
- Cable cross-section, output side **0.5-1.5 mm²**
- Wire preparation length, input side **10 mm**
- ECG lifetime **50000 h**
- Dimmable **Yes**
- Suitable for fixtures with prot. class **II**
- Overheating protection **Automatic reversible**
- Max. cable length to lamp/LED module -
- No-load proof **Yes**
- Overload protection **Automatic reversible**
- Dimming range **0.1-100 %**
- Approval marks ☐ approval **CE / C-Tick / UR**
- Standards **Acc. to EC 61347-2-13/Acc. to EN 62384/Acc. to EN 55015/Acc. to EN 61547**
- Type of protection **IP20**
- Casing material **Plastic**
- Ambient temperature range **-20-+50 °C**
- Maximum temperature at tc test point **60 °C**
- Temperature range at storage **-25-85 °C**
- Max.housing temperature in case of fault **100 °C**

Product benefits

- Safety requirement due to overload, overtemperature, short-circuit protection

Areas of application

- Suitable for indoor installations
- Separate installation (ceiling mounting)

Product features

- Intelligent digital dimmer (DALI) with constant output voltage
- Dimming range: 0.1...100 %
- Device fits also for special applications where dimming below 1 % is required

