

QT-ECO 24/220...240 S

Kod produktu: 56466



Dane techniczne:

- Operating frequency **40 kHz**
- Starting time **1.5 s**
- Length **80.0 mm**
- Mains frequency **50 Hz**
- Inrush current **13 A**
- Max. no. of ECGs on circuit breaker 10 A **36**
- Max. no. of ECGs on circuit breaker 16 A **59**
- Width **40.0 mm**
- Height **22.0 mm**
- Mounting hole spacing, length **72.0□75.0 mm**
- Product weight **50.00 g**
- Suitable for fixtures with prot. class **I / II**
- Approval marks □ approval **VDE / VDE-EMC**
- Standards **acc. to EN 61347-2-3/acc. to EN 55015:2006 + A1:2007/acc. to IEC 61000-3-2/acc. to EN 61547**
- Type of protection **IP20**
- Nominal voltage **220□240 V**
- Input voltage DC **176□254 V**
- End of lamp life safety shutdown **EOL T.2**
- EEI □ Energy Label **A3**
- Ambient temperature range **-15□+50 °C**

Product benefits

- Compact housing
- Automatic restart after lamp replacement

Areas of application

- Public buildings

Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50 Hz | 60 Hz

- Energy Efficiency Index EEI: A2
- Automatic shutdown of defective lamps and at end of life (EoL)

