

# QT-FIT5 2X14...35

Kod produktu: 56473



## Dane techniczne:

- Operating frequency **40±50 kHz**
- Width **30.0 mm**
- Product weight **181.00 g**
- Standards **acc. to EN 61347-2-3/IEC 61347-2-3/acc. to EN 55015:2006 + A1:2007 + A2:2009/acc. to EN 61000-3-2/IEC 61000-3-2/acc. to EN 61547/IEC 61547**
- Input voltage DC **198±264 V**
- Protection class **1**
- Nominal voltage **220±240 V**
- Mains frequency **50±60 Hz**
- Starting time **2.0 s**
- Length **280.0 mm**
- Height **21.0 mm**
- Mounting hole spacing, length **270.0 mm**
- Cable cross-section, input side **0.5±1.5 mm<sup>2</sup>**
- Cable cross-section, output side **0.5±1.5 mm<sup>2</sup>**
- Suitable for fixtures with prot. class **I**
- End of lamp life safety shutdown **EOL T.2**
- Approval marks □ approval **VDE / ENEC 10 / VDE-EMC**
- EEI □ Energy Label **A2**
- Ambient temperature range **-15±50 °C**

## Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

## Areas of application

- Open-plan offices, corridors and storage rooms
- Public buildings
- Strip lighting

- Suitable for emergency lighting (DC operation)
- Suitable for luminaires of protection class I
- Modernization of existing systems

#### Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50...60 Hz
- Lamp start with optimum filament preheating
- Energy Efficiency Index EEL: A2
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Lamp operation: to EN 60929
- Safety: to EN 61347-2-3

