

QTP-DL 2X55 GII

Kod produktu: 56543



Dane techniczne:

- Operating frequency **40±50 kHz**
- Starting time **1.0 s**
- Length **360.0 mm**
- Input voltage AC **198±264 V**
- Inrush current **28 A**
- Max. no. of ECGs on circuit breaker 10 A **8**
- Max. no. of ECGs on circuit breaker 16 A **13**
- Width **30.0 mm**
- Height **21.0 mm**
- Mounting hole spacing, length **350.0 mm**
- Product weight **265.00 g**
- Input voltage DC **176±276 V**
- EEI □ Energy Label **A2 BAT**
- Nominal voltage **220±240 V**
- Mains frequency **50±60 Hz**
- ECG lifetime **50000 h**
- Suitable for fixtures with prot. class **I / II**
- End of lamp life safety shutdown **EOL T.2**
- Approval marks □ approval **VDE / VDE-EMC / ENEC 10 / GOST / RCM**
- Standards **acc. to EN 61347-2-3/acc. to EN 60929/acc. to EN 55015:2006 + A1:2007/acc. to EN 61000-3-2/acc. to EN 61547**
- Type of protection **IP20**
- Ambient temperature range **-20±50 °C**

Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

Areas of application

- Emergency lighting systems acc. to EN 50172 / DIN VDE 0108-100
- Open-plan offices, corridors and storage rooms
- Public buildings
- Suitable for luminaires of protection classes I and II

Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Lamp start with optimum filament preheating
- Energy Efficiency Index EEL: A2 BAT
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Lamp operation: to EN 60929
- Safety: to EN 61347-2-3

