

HALOSPOT 48 20 W 12 V 8° GY4

Kod produktu: 56703



Dane techniczne:

- Construction wattage [PICOS] **20.00 W**
- Nominal voltage **24 V**
- Nominal wattage **20.00 W**
- Power factor λ **1.00**
- Rated wattage **20.00 W**
- Color temperature **2900 K**
- Light color as per EN 12464-1 **Warm White**
- Rated useful luminous flux 90° **150 lm**
- Color rendering index Ra **100**
- Luminous intensity **3100 cd**
- Nominal useful luminous flux 90° **150 lm**
- Beam angle **8 °**
- Starting time **0.0 s**
- Warm-up time (60 %) **0.00 s**
- Overall length **36.0 mm**
- Diameter **48.0 mm**
- Length **38.0 mm**
- Outer bulb **T9**
- Maximum diameter **48.0 mm**
- Nominal lamp life time **1000 h**
- Rated lamp life time **1000 h**
- Number of switching cycles **50000**
- Lumen main.fact.at end of nom.life time **0.75**
- Base (standard designation) **GY4**
- Mercury-free **Yes**
- Lamp mercury content **0.0 mg**
- Dimmable **Yes**
- Burning position **Any**
- Energy efficiency class **C**
- Energy consumption **22 kWh/1000h**
- Order reference **41930 SP 20W 24**
- ILCOS **HMGS//UB-20-24-GY4-48/8**

Product benefits

- Brilliant accent light
- Cap for reduced glare and ease of handling
- Excellent distribution of light thanks to faceted reflector
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Drastically reduced thermal load in fixture thanks to aluminum-coated reflector
- Contains no mercury

Areas of application

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

Product features

- Color temperature: 2,800 K
- Dimmable
- Color rendering index Ra: 100
- Diameter: 48 mm



