

DECOSTAR 35 10 W 12 V 36° GU4

Kod produktu: 56706



Dane techniczne:

- Nominal voltage **12 V**
- Nominal wattage **10.00 W**
- Color temperature **2800 K**
- Power factor λ **1.00**
- Light color as per EN 12464-1 **Warm White**
- Rated useful luminous flux 90° **90 lm**
- Beam angle **36 °**
- Starting time **0.0 s**
- Warm-up time (60 %) **0.00 s**
- Overall length **42.0 mm**
- Diameter **35.0 mm**
- Length **40.0 mm**
- Outer bulb **T9**
- Nominal lamp life time **2000 h**
- Rated lamp life time **2000 h**
- Base (standard designation) **GU4**
- Mercury-free **Yes**
- Number of switching cycles **50000**
- Dimmable **Yes**
- Energy efficiency class **B**
- Order reference **44888 WFL 10W 1**
- Color rendering index Ra **100**
- Luminous intensity **300 cd**
- Nominal useful luminous flux 90° **90 lm**
- Lumen main.fact.at end of nom.life time **0.75**
- Maximum diameter **35.0 mm**
- Lamp mercury content **0.0 mg**
- Energy consumption **11 kWh/1000h**
- ILCOS **HRGS//UB-10-12-GU4-35/36**
- Burning position **Any**
- Rated wattage **10.00 W**
- Nominal voltage **12 V**
- Power factor λ **1.00**
- Light color as per EN 12464-1 **Warm White**
- Color rendering index Ra **100**

- Starting time **0.0 s**
- Warm-up time (60 %) **0.00 s**
- Overall length **42.0 mm**
- Diameter **35.0 mm**
- Length **40.0 mm**
- Outer bulb **T9**
- Maximum diameter **35.0 mm**
- Nominal lamp life time **2000 h**
- Rated lamp life time **2000 h**
- Number of switching cycles **50000**
- Base (standard designation) **GU4**
- Mercury-free **Yes**
- Lamp mercury content **0.0 mg**
- Dimmable **Yes**
- Burning position **Any**
- Energy efficiency class **B**

Product benefits

- Brilliant accent light
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

Areas of application

- General illumination
- Workplace lighting
- Kitchen lighting
- Mirror lighting
- Object lighting
- Shops
- Restaurants, hotels and similar prestigious applications

Product features

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index Ra: 100



