

DALI PRO CONT-4 RTC

Kod produktu: 56762



Dane techniczne:

- Nominal voltage **100-240 V**
- Mains frequency **50/60 Hz**
- System wattage **20.00 W**
- Length **90.0 mm**
- Width **160.0 mm**
- Height **62.0 mm**
- Product weight **400.00 g**
- Dimming interface **DALI**
- Type of installation **DIN rail mounting**
- Number of control outputs **4**
- Type of protection **IP20**
- Protection class **I**
- Ambient temperature range **0-40 °C**

Product benefits

- Plug&Play preconfigured for instant use without any startup procedure
- Mains voltage interruption buffer battery
- All the luminaires in the system can be dimmed or switched
- Simple creation of scenes and sequences
- Switching and dimming of up to 256 DALI ECGs
- A setpoint for daylight-dependent control can be stored by double clicking
- Sensor integration in DALI

Areas of application

- Room control, floor control, daylight-dependent control
- Connection of light and presence sensors in DALI systems
- Conference rooms
- Offices: Individual and group workplaces
- Production and assembly facilities
- Suitable for indoor applications
- Large luminaire groups
- Industry

Product features

- Controller for 4 DALI lines
- Up to 50 pushbutton/sensor couplers can be integrated
- Integrated DALI supply
- 4 freely programmable switchover relays; load contact: 4x 5 A
- Daylight-dependent and/or presence-dependent or manual control
- Up to 4 x 16 groups can be controlled
- USB PC connection
- Integrated clock for event control
- Weekly scheduler
- Connection via screwless push wire terminals
- Control of lighting scenes and sequences (recall/store)
- 4 DALI lines

Equipment / Accessories

- Suitable for up to 256 electronic control gears with DALI interfaces
- Graphic configuration software with Windows user interface



