

HQL SUPER DL 80 W E27

Kod produktu: 56899



Dane techniczne:

- Nominal voltage **115 V**
- Nominal wattage **80.00 W**
- Rated lamp efficacy (standard condition) **43 lm/W**
- Lamp current **0.80000 A**
- Ignition voltage **0.198 kVp**
- Rated wattage **80.00 W**
- Color temperature **3400 K**
- Rated luminous flux **3400 lm**
- Color rendering index Ra **56**
- Rated LLMF at 4,000 h **0.84**
- Rated LLMF at 6,000 h **0.80**
- Rated LLMF at 8,000 h **0.75**
- Rated LLMF at 12,000 h **0.70**
- Rated LLMF at 16,000 h **0.63**
- Rated LLMF at 2,000 h **0.90**
- Diameter **71.0 mm**
- Length **155.0 mm**
- Product weight **56.00 g**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.99**
- Rated lamp survival factor at 6,000 h **0.99**
- Operation mode LLMF/LSF **50 Hz**
- Rated lamp survival factor at 8,000 h **0.99**
- Rated lamp survival factor at 12,000 h **0.97**
- Rated lamp survival factor at 16,000 h **0.90**
- Lifespan B50 **24000 h**
- Lifespan B10 **8000 h**
- Lifespan B5 **6000 h**
- Base (standard designation) **E27**
- Lamp mercury content **14.6 mg**
- Design / version **Coated**
- Product remark **As of April 2015 not compliant with ErP directive 245/2009**
- Dimmable **No**
- Burning position **Any**
- Enclosed luminaire required **No**

- Energy efficiency class **B**
- Energy consumption **88 kWh/1000h**
- ILCOS **QE/R-80-H/E/S-E27-71/155**
- Maximum permitted outer bulb temperature **310 °C**
- Maximum permitted base edge temperature **210 °C**

Areas of application

- Factories and workshops
- Industrial installations
- Streets
- Car parks, courtyards
- Pedestrian zones, public squares
- Parks and gardens
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

