

LF05CA2 -RGB3

Kod produktu: 56934



Dane techniczne:

- Construction wattage [PICOS] **39.00 W**
- Nominal voltage **24.00 V**
- Nominal current **1.6 A**
- Type of current **DC**
- Reverse Voltage **25 V**
- Input voltage range AC **230/25 V**
- Nominal wattage per meter **6.5 W**
- Rated wattage **72.00 W**
- Luminous flux **1080 lm**
- Light color LED **RGB**
- Nominal dominant wavelength **625 / 525 / 465 nm**
- Luminous flux per meter **180 lm**
- Beam angle **120 °**
- Length **6000.0 mm**
- Width **8.0 mm**
- Height **2.2 mm**
- Product weight **43.23 g**
- Length of smallest unit **150.0 mm**
- Lifespan **50000 h**
- New article **NEW**
- Dimmable **Yes**
- Temperature range in operation **-30/75 °C**
- Number of LEDs per module **200**
- Number of LEDs per meter **33**
- Number of LEDs per smallest unit **5**

Product benefits

- Uniform color changing
- Great design freedom thanks to flexibility and cuttability of module
- Simple mounting and connection
- Toolless connection with the optional CONNECTsystem
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back

Areas of application

- Effect lighting in architecture
- Injection of light into displays and low-profile light guides
- Dynamic effects in public zones

Product features

- Flexible and splittable LED strip with inline multichip RGB LEDs

Equipment / Accessories

- Simplified connection with optional matching CONNECTsystem
- Quick installation with optional SLIM TRACK System
- Perfectly matched to OPTOTRONIC 24 V Electronic Control Gears



