

# NAV-TS 150 W SUPER 4Y

Kod produktu: 56965



## Dane techniczne:

- Nominal voltage **97 V**
- Nominal wattage **150.00 W**
- Rated luminous flux **15000 lm**
- Diameter **23.0 mm**
- Length **138.0 mm**
- Base (standard designation) **RX7s-24**
- Lamp mercury content **23.0 mg**
- Energy consumption **165 kWh/1000h**
- ILCOS **SD-150-H/E/SL-RX7s24-23/138/H**
- Product weight **34.20 g**
- Light center length (LCL) **69.0 mm**
- Rated LLMF at 4,000 h **0.95**
- Rated LLMF at 6,000 h **0.92**
- Rated LLMF at 8,000 h **0.91**
- Rated LLMF at 12,000 h **0.89**
- Rated LLMF at 16,000 h **0.87**
- Rated LLMF at 20,000 h **0.85**
- Rated lamp efficacy (standard condition) **100 lm/W**
- Rated LLMF at 2,000 h **0.98**
- Lamp current **1.80000 A**
- Rated wattage **150.00 W**
- Ignition voltage **4.0 / 5.0 kVp**
- Color temperature **2000 K**
- Color rendering index  $R_a \leq 25$
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.98**
- Rated lamp survival factor at 6,000 h **0.98**
- Rated lamp survival factor at 8,000 h **0.97**
- Rated lamp survival factor at 12,000 h **0.96**
- Rated lamp survival factor at 16,000 h **0.95**
- Rated lamp survival factor at 20,000 h **0.90**
- Lifespan B50 **28000 h**
- Lifespan B10 **20000 h**
- Lifespan B5 **16000 h**
- Design / version **Clear**

- Dimmable **Yes**
- Burning position **p45**
- Enclosed luminaire required **No**
- Hot restart **Yes**
- Energy efficiency class **A+**
- Maximum permitted outer bulb temperature **650 °C**
- Maximum permitted pinch temperature **250 °C**

#### Areas of application

- Industrial installations
- Car parks, courtyards
- Buildings, monuments, bridges
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

#### Product features

- Lamp survival factor: 95 % after 16,000 hours burning time

