

NAV-TS 400 W FC2

Kod produktu: 56967



Dane techniczne:

- Nominal voltage **105 V**
- Nominal wattage **400.00 W**
- Rated luminous flux **49000 lm**
- Energy consumption **440 kWh/1000h**
- ILCOS **SD-400-H/E/SL-Fc2-23/206/H**
- Product weight **70.00 g**
- Rated lamp efficacy (standard condition) **123 lm/W**
- Lamp current **4.45000 A**
- Rated wattage **400.00 W**
- Ignition voltage **4.0 / 5.0 kVp**
- Color temperature **2000 K**
- Color rendering index $R_a \leq 25$
- Rated LLMF at 4,000 h **0.96**
- Rated LLMF at 6,000 h **0.94**
- Rated LLMF at 8,000 h **0.93**
- Rated LLMF at 12,000 h **0.91**
- Rated LLMF at 16,000 h **0.90**
- Rated LLMF at 20,000 h **0.88**
- Rated LLMF at 2,000 h **0.97**
- Diameter **23.0 mm**
- Length **206.0 mm**
- Light center length (LCL) **103.0 mm**
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.98**
- Rated lamp survival factor at 6,000 h **0.97**
- Rated lamp survival factor at 8,000 h **0.96**
- Rated lamp survival factor at 12,000 h **0.95**
- Rated lamp survival factor at 16,000 h **0.90**
- Rated lamp survival factor at 20,000 h **0.75**
- Lifespan B50 **24000 h**
- Lifespan B10 **16000 h**
- Lifespan B5 **12000 h**
- Base (standard designation) **Fc2**
- Lamp mercury content **24.0 mg**
- Design / version **Clear**

- Dimmable **Yes**
- Burning position **p45**
- Enclosed luminaire required **No**
- Hot restart **Yes**
- Energy efficiency class **A+**
- Maximum permitted outer bulb temperature **650 °C**
- Maximum permitted pinch temperature **250 °C**

Areas of application

- Industrial installations
- Car parks, courtyards
- Buildings, monuments, bridges
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product features

- Lamp survival factor: 95 % after 12,000 hours burning time

