

NAV-TS 70 W SUPER 4Y

Kod produktu: 56968



Dane techniczne:

- Nominal voltage **85 V**
- Nominal wattage **70.00 W**
- Rated luminous flux **6600 lm**
- Diameter **20.0 mm**
- Length **120.0 mm**
- Base (standard designation) **RX7s**
- Lamp mercury content **18.0 mg**
- Energy consumption **77 kWh/1000h**
- ILCOS **SD-70-H/E/SL-RX7s-20/120/H**
- Product weight **20.80 g**
- Light center length (LCL) **60.0 mm**
- Rated LLMF at 4,000 h **0.90**
- Rated LLMF at 6,000 h **0.88**
- Rated LLMF at 8,000 h **0.86**
- Rated LLMF at 12,000 h **0.83**
- Rated LLMF at 16,000 h **0.81**
- Rated LLMF at 20,000 h **0.80**
- Rated lamp efficacy (standard condition) **94 lm/W**
- Rated LLMF at 2,000 h **0.94**
- Lamp current **0.98000 A**
- Rated wattage **70.00 W**
- Ignition voltage **4.0 / 5.0 kVp**
- Color temperature **2000 K**
- Color rendering index $R_a \leq 25$
- Rated lamp survival factor at 2,000 h **0.99**
- Rated lamp survival factor at 4,000 h **0.98**
- Rated lamp survival factor at 6,000 h **0.98**
- Rated lamp survival factor at 8,000 h **0.97**
- Rated lamp survival factor at 12,000 h **0.96**
- Rated lamp survival factor at 16,000 h **0.95**
- Rated lamp survival factor at 20,000 h **0.90**
- Lifespan B50 **28000 h**
- Lifespan B10 **20000 h**
- Lifespan B5 **16000 h**
- Design / version **Clear**

- Dimmable **Yes**
- Burning position **p45**
- Enclosed luminaire required **No**
- Hot restart **Yes**
- Energy efficiency class **A+**
- Maximum permitted outer bulb temperature **650 °C**
- Maximum permitted pinch temperature **250 °C**

Areas of application

- Industrial installations
- Car parks, courtyards
- Buildings, monuments, bridges
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product features

- Lamp survival factor: 95 % after 16,000 hours burning time

