

QT-FQ 2X80

Kod produktu: 57027



Dane techniczne:

- Nominal voltage **220□240 V**
- Operating frequency **70□75 kHz**
- Input voltage AC **198□264 V**
- Mains frequency **50□60 Hz**
- Inrush current **39 A**
- Max. no. of ECGs on circuit breaker 10 A **5**
- Max. no. of ECGs on circuit breaker 16 A **9**
- Input voltage DC -
- Starting time **1.0 s**
- Length **423.0 mm**
- Width **30.0 mm**
- Height **21.0 mm**
- Mounting hole spacing, length **415.0 mm**
- Product weight **381.00 g**
- ECG lifetime **50000 h**
- Suitable for fixtures with prot. class **I / II**
- End of lamp life safety shutdown **EOL T.2**
- Approval marks □ approval **VDE / VDE-EMC / ENEC 10 / GOST / RCM**
- Standards **acc. to EN 55015, CISPR 15/acc. to EN 61547/IEC 61547/acc. to EN 61000-3-2/IEC 61000-3-2/acc. to EN 61347-2-3/IEC 61347-2-3**
- Type of protection **IP20**
- EEI □ Energy Label **A2**
- Ambient temperature range **-20□+50 °C**

Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

Areas of application

- Industry
- Open-plan offices, corridors and storage rooms
- Public buildings
- Sports halls and factories
- Strip lighting
- Modernization of existing systems

Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50 Hz | 60 Hz
- Lamp start with optimum filament preheating
- Lifetime: up to 100,000 h (temperature at $T_c = 65\text{ }^{\circ}\text{C}$, max. 10 % failure rate)
- Energy Efficiency Index EEL: A2
- Safety: to EN 61347-2-3
- Automatic shutdown of defective lamps and at end of life (EoL T.2)

