

DALI LS/PD LI

Kod produktu: 57078



Dane techniczne:

- Length **48.0 mm**
- Width **15.0 mm**
- Height **17.0 mm**
- Product weight **10.00 g**
- Type of installation **Ceiling integration/Luminaire integration**
- Detection angle **80 °**
- Detection area **6 m²**
- Maximum installation height **5 m**
- Operating range, light sensor **20000 lx**
- Type of protection **IP20**
- Product color **Grey**
- Ambient temperature range **0÷+50 °C**

Product benefits

- Small housing design
- Presence detection angle adjustable between 40...90° via integrated shutters
- Can be addressed via DALI
- Compact housing for luminaire installation
- Daylight-dependent control with automatic shutdown in adequate daylight
- Slim housing design and flexible mounting concept
- Power supply from DALI
- DALI based light management system integrable into building management systems

Areas of application

- Installation in industry and office luminaires
- Ceiling installation via LS/PD CI KIT or LS/PD AP KIT possible
- Classrooms
- Conference rooms
- Corridors
- Individual offices
- Suspended luminaires
- Suitable for indoor applications

Product features

- Direct connection to DALI
- Light and presence sensor for luminaire installation
- Presence detection via passive IR element
- Light sensor working range: 20...800 lx (measured at sensor)
- Function indicator with two-color LED
- Flame-resistant, halogen free polycarbonate plastic housing
- Mounting height: 2...5 m

Equipment / Accessories

- Suitable for DALI Professional and DALIeco Control unit
- Attachable mounting frame for luminaire mounting from inside and outside

