

QT-FIT 5/8 1X18...39

Kod produktu: 57107



Dane techniczne:

- Nominal voltage **220□240 V**
- Operating frequency **40□50 kHz**
- Starting time **2.0 s**
- Length **280.0 mm**
- Input voltage AC **198□264 V**
- Mains frequency **50□60 Hz**
- Inrush current **24 A**
- Max. no. of ECGs on circuit breaker 10 A **17**
- Max. no. of ECGs on circuit breaker 16 A **28**
- Width **30.0 mm**
- Height **21.0 mm**
- Mounting hole spacing, length **270.0 mm**
- Cable cross-section, input side **0.5□1.5 mm²**
- Product weight **154.00 g**
- Cable cross-section, output side **0.5□1.5 mm²**
- Ambient temperature range **-15□+50 °C**
- ECG lifetime **50000 h**
- Suitable for fixtures with prot. class **I**
- Approval marks □ approval **CE / VDE / ENEC 10 / VDE-EMC**
- Standards **Acc. to EN 61347-2-3/IEC 61347-2-3/Acc. to EN 55015:2006 + A1:2007 + A2:2009/Acc. to EN 61000-3-2/IEC 61000-3-2/Acc. to EN 61547/IEC 61547**
- Type of protection **IP20**
- Input voltage DC **185□264 V**
- EEI □ Energy Label **A2**
- End of lamp life safety shutdown **EOL T.2**
- Protection class **I**
- Nominal voltage **220□240 V**
- Operating frequency **40□50 kHz**
- Input voltage AC **198□264 V**
- Mains frequency **50□60 Hz**
- Input voltage DC **185□264 V**
- Starting time **2.0 s**
- Length **280.0 mm**
- Width **30.0 mm**
- Height **21.0 mm**

- Mounting hole spacing, length **270.0 mm**
- Cable cross-section, input side **0.5□1.5 mm²**
- Cable cross-section, output side **0.5□1.5 mm²**
- ECG lifetime **50000 h**
- Suitable for fixtures with prot. class **I**
- End of lamp life safety shutdown **EOL T.2**
- Approval marks □ approval **CE / VDE / ENEC 10 / VDE-EMC**
- Standards **Acc. to EN 61347-2-3/IEC 61347-2-3/Acc. to EN 55015:2006 + A1:2007 + A2:2009/Acc. to EN 61000-3-2/IEC 61000-3-2/Acc. to EN 61547/IEC 61547**
- Type of protection **IP20**
- EEI □ Energy Label **A2**
- Protection class **I**
- Ambient temperature range **-15□+50 °C**

Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

Areas of application

- Open-plan offices, corridors and storage rooms
- Public buildings
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Suitable for luminaires of protection class I
- Modernization of existing systems

Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- Line frequency: 50...60 Hz
- Lamp start with optimum filament preheating
- Energy Efficiency Index EEI: A2
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Lamp operation: to EN 60929
- Safety: to EN 61347-2-3

