QTz8 1X18

Kod produktu: 57108



Dane techniczne:

- Nominal voltage **220240 V**
- Operating frequency **3045 kHz**
- Length **150.0 mm**
- Mains frequency **50/60 Hz**
- Width **40.0 mm**
- Height **28.0 mm**
- Mounting hole spacing, length **140.0 mm**
- Product weight **100.00 g**
- Ambient temperature range **-15+50 °C**
- Suitable for fixtures with prot. class **I**
- Approval marks approval **CE** / **CQC**
- Type of protection **IP20**
- EEI Energy Label **A2**
- Nominal voltage **220240 V**
- Operating frequency **3045 kHz**
- Mains frequency **50/60 Hz**
- Width **40.0 mm**
- Suitable for fixtures with prot. class **I**
- Approval marks approval **CE** / **CQC**
- Type of protection **IP20**
- EEI Energy Label **A2**
- Ambient temperature range **-15+50 °C**

Product benefits

- Compact housing
- Automatic restart after lamp replacement


Areas of application

- Public buildings
- Sports halls
- Strip lighting
- Suitable for luminaires of protection class I

biuro@elektriko.pl +48 737 449 514

Product features

- Supply voltage: 220…240 V
- Line voltage: 198…264 V
- Line frequency: 50 Hz | 60 Hz
- Energy Efficiency Index EEI: A2



biuro@elektriko.pl +48 737 449 514