

App 15W E14 230-240V T22 CL OV 1CT

Kod produktu: 57360



Dane techniczne:

- Cap-Base **E14**
- Bulb **T22 [T 22mm]**
- Rated Lifetime (hours) **1000 hr**
- Color Temperature **2700 K**
- Rated Luminous Flux **90 Lm**
- Power Factor **1 -**
- Voltage **230-240 V**
- Dimmable **Yes**
- Rated Wattage **15.0 W**
- Starting Time **0.0 s**
- Energy Efficiency Label (EEL) **E**
- Energy consumption kWh/1000h **15 kWh**
- Switching cycle **4000X**
- Diameter D **22 (max) mm**
- Overall Length C **49 (max) mm**
- Full product code **924196244440**
- Full product name **Appliance 15W E14 230-240V T22 CL OV 1CT**
- Order code **924196244440**
- Order product name **App 15W E14 230-240V T22 CL OV 1CT**
- Packing configuration **10X10F**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500257673**
- Bar code on pack - EAN1 **8711500036599**
- Packs per outerbox **100**
- Logistic code(s) - 12NC **924196244440**
- Net weight per piece **10.500 gr**
- Warm-up Time to 60% Light Outp **instant full light**
- Bulb Finish **Clear**
- Main Application **Oven**
- Bar code on intermediate packing - EAN2 **8711500255174**
- Lamp Wattage **15 W**
- Nominal Lifetime **1000 hr**
- Operating Position **any [Any or Universal (U)]**
- Rated Lifetime (years) **1 an**
- Color Rendering Index **100 Ra8**

- ILCOS code **IBT/C-15-230/240-E14-22***
- Luminous flux lamp **90 Lm**
- Lamp Wattage Technical **15.0 W**
- Lamp Current **0.06 A**

Tubular vacuum lamps with clear glass (T-bulb)

Tubular vacuum lamps with clear glass (T-bulb)

Features

Coiled-coil filament

Manufactured with heat-resistant solder, getter and lamp-base cement

Applications

Electrical and standard ovens, rotisseries and similar places subject to high operating temperatures

Available for specific oven luminaires fitted in different positions such as downlighter, side-light and backlight



