

App 25W E14 230-240V T25 CL OV 1CT

Kod produktu: 57366



Dane techniczne:

- Cap-Base **E14**
- Bulb **T25 [T 25mm]**
- Rated Lifetime (hours) **1000 hr**
- Color Temperature **2700 K**
- Rated Luminous Flux **172 Lm**
- Power Factor **1 -**
- Voltage **230-240 V**
- Dimmable **Yes**
- Rated Wattage **25.0 W**
- Starting Time **0.0 s**
- Energy Efficiency Label (EEL) **E**
- Energy consumption kWh/1000h **25 kWh**
- Switching cycle **4000X**
- Diameter D **25 (max) mm**
- Overall Length C **57 (max) mm**
- Full product code **921098244433**
- Full product name **Appliance 25W E14 230-240V T25 CL OV 1CT**
- Order code **921098244433**
- Order product name **App 25W E14 230-240V T25 CL OV 1CT**
- Packing configuration **10X10F**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8727900947144**
- Bar code on pack - EAN1 **8727900947120**
- Packs per outerbox **100**
- Logistic code(s) - 12NC **921098244433**
- Net weight per piece **13.000 gr**
- Warm-up Time to 60% Light Outp **instant full light**
- Bulb Finish **Clear**
- Main Application **Oven**
- Bar code on intermediate packing - EAN2 **8727900947137**
- Lamp Wattage **25 W**
- Nominal Lifetime **1000 hr**
- Operating Position **any [Any or Universal (U)]**
- Rated Lifetime (years) **1 an**
- Color Rendering Index **100 Ra8**

- ILCOS code **IBT/C-25-230/240-E14-25***
- Luminous flux lamp **172 Lm**
- Lamp Wattage Technical **25.0 W**
- Lamp Current **0.11 A**

Tubular vacuum lamps with clear glass (T-bulb)

Tubular vacuum lamps with clear glass (T-bulb)

Features

Coiled-coil filament

Manufactured with heat-resistant solder, getter and lamp-base cement

Applications

Electrical and standard ovens, rotisseries and similar places subject to high operating temperatures

Available for specific oven luminaires fitted in different positions such as downlighter, side-light and backlight



