

Appl 40W E14 240V P45 CL OV 1BL/10

Kod produktu: 57368



Dane techniczne:

- Cap-Base **E14**
- Bulb **P45 [P 45mm]**
- Rated Lifetime (hours) **1000 hr**
- Color Temperature **2700 K**
- Rated Luminous Flux **420 Lm**
- Power Factor **1 -**
- Voltage **240 V**
- Dimmable **Yes**
- Rated Wattage **40.0 W**
- Starting Time **0.0 s**
- Energy Efficiency Label (EEL) **E**
- Energy consumption kWh/1000h **40 kWh**
- Switching cycle **4000X**
- Diameter D **45 mm**
- Overall Length C **75 (max) mm**
- Full product code **923265945508**
- Full product name **Appliance 40W E14 240V P45 CL OV 1BL**
- Order code **923265945508**
- Order product name **Appl 40W E14 240V P45 CL OV 1BL/10**
- Packing configuration **10**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500158727**
- Bar code on pack - EAN1 **8711500157546**
- Packs per outerbox **10**
- Logistic code(s) - 12NC **923265945508**
- Net weight per piece **15.460 gr**
- Warm-up Time to 60% Light Outp **instant full light**
- Bulb Finish **Clear**
- Main Application **Oven**
- Lamp Wattage **40 W**
- Nominal Lifetime **1000 hr**
- Operating Position **any [Any or Universal (U)]**
- Rated Lifetime (years) **1 an**
- Color Rendering Index **100 Ra8**
- ILCOS code **IBP/C-40-240-E14-45***

- Luminous flux lamp **420 Lm**
- Lamp Current **0.17 A**

Lustre vacuum lamps with clear glass (P-bulb)

Lustre vacuum lamps with clear glass (P-bulb)

Features

Coiled-coil filament

Manufactured with heat-resistant solder, getter and lamp-base cement

Applications

Electrical and standard ovens, rotisseries and similar places subject to high operating temperatures

Available for specific oven luminaires fitted in different positions such as downlighter, side-light and backlight



