

# Brill 50W GU5.3 12V 60D 1CT/10X5F

Kod produktu: 57396



## Dane techniczne:

- Cap-Base **GU5.3**
- Bulb **MR16 [2inch/50mm]**
- Rated Lifetime (hours) **4000 hr**
- Color Temperature **3000 K**
- LLMF - end nominal lifetime **80 (min) %**
- Rated Luminous Flux **775 Lm**
- Power Factor **1 -**
- Voltage **12 V**
- Dimmable **Yes**
- Rated Wattage **50.0 W**
- Starting Time **0.0 s**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **53 kWh**
- Switching cycle **16000X**
- Diameter D **51 (max) mm**
- Overall Length C **46 (max) mm**
- Full product code **924051117101**
- Full product name **Brilliantline Dichroic 50W GU5.3 12V MR16 60D 1CT**
- Order code **924051117101**
- Order product name **Brilliantline Dichroic 50W GU5.3 12V MR16 60D 1CT**
- Packing configuration **10X5F**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500425218**
- Bar code on pack - EAN1 **8711500425195**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **924051117101**
- Net weight per piece **30.000 gr**
- Warm-up Time to 60% Light Outp **instant full light**
- Bulb Finish **Clear**
- Beam Angle **60 D**
- Luminous Intensity **1065 (max) cd**
- Luminous flux in 90° cone **775 Lm**
- Rated Beam Angle **60 D**
- Bar code on intermediate packing - EAN2 **8711500425201**
- Lamp Wattage **50 W**

- Nominal Lifetime **4000 hr**
- Operating Position **any [Any or Universal (U)]**
- Rated Lifetime (years) **4 an**
- Beam Angle Technical **60 D**
- Color Rendering Index **100 Ra8**
- ILCOS code **HRGS-50-12-GU5.3-50/60**
- Cap-Base Temperature **350 (max) C**
- Lamp Wattage Technical **51 W**
- Lamp Current **4.2 A**
- Bulb Temperature **250 (max) C**
- ANSI Code Halogen **na**
- Philips Code **14621**
- Life to 50% failures **4000 hr**
- Color Temperature Technical **3000 K**

Superior-quality low-voltage halogen burner in glass reflector. Ideal solution for small decorative luminaires, putting your objects in the spotlight. Dichroic coating prevents heat transmission onto the object.



