

Plusline ES 78mm 2y 48W R7s 230V 1BB

Kod produktu: 57523



Dane techniczne:

- Cap-Base **R7s**
- Bulb **T4 [T4: .434 inch / 11mm]**
- Rated Lifetime (hours) **2000 hr**
- Color Temperature **2900 K**
- Luminous Efficacy Lamp **15.6 Lm/W**
- LLMF - end nominal lifetime **80 (min) %**
- Rated Luminous Flux **750 Lm**
- Power Factor **1 -**
- Voltage **230 V**
- Dimmable **Yes**
- Rated Wattage **48.0 W**
- Wattage Equivalent **60 W**
- Starting Time **0.0 s**
- Energy Efficiency Label (EEL) **D**
- Energy consumption kWh/1000h **48 kWh**
- Switching cycle **8000X**
- Diameter D **11 (max) mm**
- Overall Length C **78 (max) mm**
- Full product code **924587044210**
- Full product name **Plusline ES Compact 78mm 2y 48W R7s 230V 1BB**
- Order code **924587044210**
- Order product name **Plusline ES 78mm 2y 48W R7s 230V 1BB**
- Packing configuration **10X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8727900852332**
- Bar code on pack - EAN1 **8727900852318**
- Packs per outerbox **100**
- Logistic code(s) - 12NC **924587044210**
- Net weight per piece **7.000 gr**
- Warm-up Time to 60% Light Outp **instant full light**
- Bulb Finish **Clear**
- Bar code on intermediate packing - EAN2 **8727900852325**
- Cap-Base Information **18**
- Lamp Wattage **48 W**
- Nominal Lifetime **2000 hr**
- Operating Position **any [Any or Universal (U)]**
- Rated Lifetime (years) **2 an**
- Color Rendering Index **100 Ra8**

- Luminous flux lamp **780 Lm**
- Lamp Wattage Technical **48 W**
- Lamp Current **0.21 A**
- Bulb Temperature **900 (max) C**
- Pinch Temperature **350 (max) C**
- Life to 50% failures **2000 hr**
- Color Temperature Technical **2900 K**
- Insertion Length B **73.3 (min), 74.9 (nom), 76.5 (max) mm**

Mains-voltage halogen linear lamp with superior energy efficiency. Offers very long lifetime and crisp halogen light. Ideal solution for decorative luminaires.

Mains-voltage halogen linear lamp with superior energy efficiency. Offers very long lifetime and crisp halogen light. Ideal solution for decorative luminaires.

Features

Superior quality of light with excellent color rendering (Ra=100)

Same size for direct replacement of existing halogen lamps

Lifetime: 2000 hours

Universal burning position

Instant start

Applications

General lighting in shops, restaurants, hotels, galleries, exhibitions and museums. Decorative outdoor: billboards, exhibitions and parking areas



