

Softone Globe 20W WW E27 G120 1CH/4

Kod produktu: 57554



Dane techniczne:

- Cap-Base **E27**
- Bulb **G120 [G 120mm]**
- Rated Lifetime (hours) **10000 hr**
- Color Code **827 [CCT of 2700K]**
- Color Designation (text) **Warm White**
- Color Temperature **2700 K**
- Luminous Efficacy Lamp **57 Lm/W**
- LLMF - end nominal lifetime **65 %**
- Rated Luminous Flux **1140 Lm**
- Lamp Current mA **141 mA**
- Line Frequency **50/60 Hz**
- Power Factor **0.6 -**
- Voltage **220-240 V**
- Dimmable **No**
- Rated Wattage **20.0 W**
- Wattage Equivalent **85 W**
- Starting Time **0.3 s**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **20 kWh**
- Switching cycle **30000X**
- Diameter D **121 (max) mm**
- Overall Length C **182 (max) mm**
- Full product code **929689171103**
- Full product name **Softone Globe 20W WW E27 G120 1CH**
- Order code **929689171103**
- Order product name **Softone Globe 20W WW E27 G120 1CH/4**
- Packing configuration **4**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500830975**
- Bar code on pack - EAN1 **8711500830159**
- Packs per outerbox **4**
- Logistic code(s) - 12NC **929689171103**
- Net weight per piece **0.160 kg**
- Warm-up Time to 60% Light Outp **10 (min), 100 (max) s**
- Lamp Wattage **20 W**

- Nominal Lifetime **10000 hr**
- Rated Lifetime (years) **10 an**
- Color Rendering Index **81 (min), 82 (nom) Ra8**
- Luminous flux lamp **1140 Lm**
- Color Temperature Technical **2700 K**
- Mercury (Hg) Content **1.5 (nom), 2.0 (max) mg**
- Lumen Maintenance 2000h **83 %**
- Chromaticity Coordinate X **463 -**
- Chromaticity Coordinate Y **420 -**
- Lumen Maintenance 6000h **70 %**
- Width F **48.2 (max) mm**

Decorative covered energy-saving lamps in Globe shape, for consumer applications. The product family includes different size globe, which enables easy replacement of most incandescent lamp all the way.

Decorative covered energy-saving lamps in Globe shape, for consumer applications. The product family includes different size globe, which enables easy replacement of most incandescent lamp all the way.

Features

Long-life and Energy saving alternative to incandescent lamps

Suitable for frequent switching

Recommended ambient temperature range to ensure almost constant light output (>90%): between 0 and +50°C

Flawless ignition at -10°C and up

Applications

Designed for incandescent lamp replacement in (open) luminaires with a decorative function or as replacement of globe incandescent lamps

Especially suitable for applications with a decorative function in areas where lighting is required for longer periods of time or where lamp replacement is difficult

Not suitable for dimming and electronic devices



