

MASTER PL-S 11W/840/4P 1CT/5X10BOX

Kod produktu: 57664



Dane techniczne:

- Cap-Base **2G7**
- Color Code **840 [CCT of 4000K]**
- Color Designation (text) **Cool White**
- Color Temperature **4000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **13 kWh**
- Diameter D **28 (max) mm**
- Overall Length C **219.9 (max) mm**
- Full product code **927936684011**
- Full product name **MASTER PL-S 11W/840/4P 1CT**
- Order code **927936684011**
- Order product name **MASTER PL-S 11W/840/4P 1CT/5X10BOX**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500261243**
- Bar code on pack - EAN1 **8711500261229**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927936684011**
- Net weight per piece **41.000 gr**
- Bar code on intermediate packing - EAN2 **8711500261236**
- Cap-Base Information **4P**
- Lamp Wattage **11 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSD-11/40/1B-E-2G7**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **214 (max) mm**
- Chromaticity Coordinate X **381 -**
- Chromaticity Coordinate Y **379 -**
- Lum Efficacy Rated EM 25°C **82 Lm/W**
- Luminous Flux EM 25°C, Nominal **900 Lm**
- Luminous Flux EM 25°C, Rated **900 Lm**
- Design Temperature **28 C**
- Lamp Wattage EM 25°C, Nominal **11 W**
- Lamp Current EM 25°C **0.160 A**

- Lamp Voltage EM 25°C **89 V**
- Lamp Wattage EM 25°C, Rated **11.6 W**
- Base Face to Base Face A **196 (max) mm**
- Diameter D1 **13 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **66 %**
- LSF HF Preheat 6000h Rated,3h **97 %**
- LSF HF Preheat 8000h Rated,3h **92 %**
- LSF HF Preheat 16000h Rated,3h **30 %**
- Luminous Flux EL 25°C, Nominal **900 Lm**
- Luminous Flux EL 25°C, Rated **900 Lm**
- LLMF HF 2000h Rated **95 %**
- LLMF HF 4000h Rated **92 %**
- LLMF HF 12000h Rated **86 %**
- LLMF HF 6000h Rated **90 %**
- LLMF HF 8000h Rated **88 %**
- Lamp Wattage EL 25°C, Rated **11.0 W**
- Lamp Voltage EL 25°C **89 V**
- Lamp Wattage EL 25°C, Nominal **11 W**
- Lamp Current EL 25°C **0.160 A**

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic gear and is provided with a plug-in/pull-out lamp base.

Features

4-pin base

Fluorescent tri-phosphor technology

Low light depreciation over lamp life

Applications

Designed for use in hotels, restaurants, theatres and homes

Suitable for use in signs, corridors, security and orientation lighting



