

MASTER PL-S 7W/827/2P 1CT/5X10BOX

Kod produktu: 57669



Dane techniczne:

- Cap-Base **G23 [Two-Pin Compact Fluorescent; low preheat current; two retainers]**
- Color Code **827 [CCT of 2700K]**
- Color Designation (text) **Incandescent White**
- Color Temperature **2700 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **9 kWh**
- Diameter D **28 (max) mm**
- Overall Length C **135 (max) mm**
- Full product code **927935682711**
- Full product name **MASTER PL-S 7W/827/2P 1CT**
- Order code **927935682711**
- Order product name **MASTER PL-S 7W/827/2P 1CT/5X10BOX**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500260598**
- Bar code on pack - EAN1 **8711500260574**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927935682711**
- Net weight per piece **26.000 gr**
- Bar code on intermediate packing - EAN2 **8711500260581**
- Cap-Base Information **2P**
- Lamp Wattage **7 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSD-7/27/1B-I-G23**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **113 (max) mm**
- Chromaticity Coordinate X **455 -**
- Chromaticity Coordinate Y **417 -**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **98 %**
- LSF EM 6000h Rated,3h cycle **95 %**
- LSF EM 8000h Rated,3h cycle **86 %**
- LLMF EM 2000h Rated **94 %**
- Lum Efficacy Rated EM 25°C **57 Lm/W**

- Luminous Flux EM 25°C, Nominal **400 Lm**
- Luminous Flux EM 25°C, Rated **405 Lm**
- LLMF EM 4000h Rated **91 %**
- LLMF EM 6000h Rated **89 %**
- LLMF EM 8000h Rated **86 %**
- Design Temperature **28 C**
- Lamp Wattage EM 25°C, Nominal **7 W**
- Lamp Current EM 25°C **0.175 A**
- Lamp Voltage EM 25°C **47 V**
- Lamp Wattage EM 25°C, Rated **7.1 W**
- Base Face to Base Face A **97 (max) mm**
- Diameter D1 **13 (max) mm**

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base

Features

2-pin base with a housing incorporating the special instant starter and capacitor

Fluorescent tri-phosphor technology

Low light depreciation over lamp life



