

# MASTER PL-C 13W/827/2P 1CT/5X10BOX

Kod produktu: 57685



## Dane techniczne:

- Cap-Base **G24d-1**
- Color Code **827 [CCT of 2700K]**
- Color Designation (text) **Incandescent White**
- Color Temperature **2700 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **17 kWh**
- Diameter D **27.1 (max) mm**
- Overall Length C **138.4 (max) mm**
- Full product code **927904882740**
- Full product name **MASTER PL-C 13W/827/2P 1CT**
- Order code **927904882740**
- Order product name **MASTER PL-C 13W/827/2P 1CT/5X10CC**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500715647**
- Bar code on pack - EAN1 **8711500620811**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927904882740**
- Net weight per piece **53.600 gr**
- Bar code on intermediate packing - EAN2 **8711500621023**
- Cap-Base Information **2P**
- Lamp Wattage **13 W**
- Color Rendering Index **83 Ra8**
- ILCOS code **FSQ-13/27/1B-I-G24d=1**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **116.0 (max) mm**
- Chromaticity Coordinate X **463 -**
- Chromaticity Coordinate Y **420 -**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **98 %**
- LSF EM 6000h Rated,3h cycle **92 %**
- LSF EM 8000h Rated,3h cycle **78 %**
- LLMF EM 2000h Rated **92 %**
- Lum Efficacy Rated EM 25°C **67 Lm/W**

- Luminous Flux EM 25°C, Nominal **900 Lm**
- Luminous Flux EM 25°C, Rated **900 Lm**
- LLMF EM 4000h Rated **87 %**
- LLMF EM 6000h Rated **84 %**
- LLMF EM 8000h Rated **81 %**
- Design Temperature **28 C**
- Lamp Wattage EM 25°C, Nominal **13 W**
- Lamp Current EM 25°C **0.170 A**
- Lamp Voltage EM 25°C **95 V**
- Lamp Wattage EM 25°C, Rated **13.4 W**
- Base Face to Base Face A **97.7 (max) mm**
- Diameter D1 **27.1 (max) mm**

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

## Features

2-pin base with a housing incorporating the special instant starter

Fluorescent tri-phosphor technology

Low light depreciation over lamp life

## Applications

Designed for general or supplementary lighting in professional or home environments

Recessed or surface-mounted downlighters, wall units, table lamps and pendant lamps



