

# MASTER PL-C 13W/830/4P 1CT/5X10BOX

Kod produktu: 57687



## Dane techniczne:

- Cap-Base **G24q-1**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **15 kWh**
- Diameter D **27.1 (max) mm**
- Overall Length C **130.9 (max) mm**
- Full product code **927907183001**
- Full product name **MASTER PL-C 13W/830/4P 1CT**
- Order code **927907183001**
- Order product name **MASTER PL-C 13W/830/4P 1CT/5X10CC**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500715722**
- Bar code on pack - EAN1 **8711500623317**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927907183001**
- Net weight per piece **0.060 kg**
- Bar code on intermediate packing - EAN2 **8711500271860**
- Cap-Base Information **4P**
- Lamp Wattage **13 W**
- Color Rendering Index **83 Ra8**
- ILCOS code **FSQ-13/30/1B-E-G24q=1**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **116.0 (max) mm**
- Chromaticity Coordinate X **440 -**
- Chromaticity Coordinate Y **403 -**
- Lum Efficacy Rated EM 25°C **69 Lm/W**
- Luminous Flux EM 25°C, Nominal **900 Lm**
- Luminous Flux EM 25°C, Rated **900 Lm**
- Design Temperature **28 C**
- Lamp Current EM 25°C **0.170 A**
- Lamp Voltage EM 25°C **95 V**

- Lamp Wattage EM 25°C, Rated **13.0 W**
- Base Face to Base Face A **97.7 (max) mm**
- Diameter D1 **27.1 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **80 %**
- LSF HF Preheat 6000h Rated,3h **95 %**
- LSF HF Preheat 8000h Rated,3h **90 %**
- LSF HF Preheat 16000h Rated,3h **65 %**
- Luminous Flux EL 25°C, Nominal **900 Lm**
- Luminous Flux EL 25°C, Rated **900 Lm**
- LLMF HF 2000h Rated **99 %**
- LLMF HF 4000h Rated **88 %**
- LLMF HF 6000h Rated **85 %**
- LLMF HF 8000h Rated **83 %**
- Lamp Wattage EL 25°C, Rated **12.5 W**
- Lamp Voltage EL 25°C **95 V**
- Lamp Wattage EL 25°C, Nominal **13 W**
- Lamp Current EL 25°C **0.170 A**
- Lum Efficacy Rated HF 25°C **72 Lm/W**
- LSF HF Preheat 20000h Rated,3h **50 %**

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 4-pin version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

## Features

4-pin base

Fluorescent tri-phosphor technology

Low light depreciation over lamp life

## Applications

Designed for general or supplementary lighting in professional or home environments

Recessed or surface-mounted downlighters, wall units, table lamps and pendant lamps



