

MASTER PL-C 10W/840/2P 1CT/5X10BOX

Kod produktu: 57691



Dane techniczne:

- Cap-Base **G24d-1**
- Color Code **840 [CCT of 4000K]**
- Color Designation (text) **Cool White**
- Color Temperature **4000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **13 kWh**
- Diameter D **27.1 (max) mm**
- Overall Length C **116.4 (max) mm**
- Full product code **927903884040**
- Full product name **MASTER PL-C 10W/840/2P 1CT**
- Order code **927903884040**
- Order product name **MASTER PL-C 10W/840/2P 1CT/5X10CC**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500710994**
- Bar code on pack - EAN1 **8711500704986**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927903884040**
- Net weight per piece **45.000 gr**
- Bar code on intermediate packing - EAN2 **8711500733030**
- Cap-Base Information **2P**
- Lamp Wattage **10 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSQ-10/40/1B-I-G24d=1**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **94.0 (max) mm**
- Chromaticity Coordinate X **380 -**
- Chromaticity Coordinate Y **380 -**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **98 %**
- LSF EM 6000h Rated,3h cycle **92 %**
- LSF EM 8000h Rated,3h cycle **78 %**
- LLMF EM 2000h Rated **92 %**
- Lum Efficacy Rated EM 25°C **60 Lm/W**

- Luminous Flux EM 25°C, Nominal **600 Lm**
- Luminous Flux EM 25°C, Rated **600 Lm**
- LLMF EM 4000h Rated **87 %**
- LLMF EM 6000h Rated **84 %**
- LLMF EM 8000h Rated **81 %**
- Design Temperature **28 C**
- Lamp Wattage EM 25°C, Nominal **10 W**
- Lamp Current EM 25°C **0.190 A**
- Lamp Voltage EM 25°C **63 V**
- Lamp Wattage EM 25°C, Rated **10.0 W**
- Base Face to Base Face A **75.7 (max) mm**
- Diameter D1 **27.1 (max) mm**

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Features

2-pin base with a housing incorporating the special instant starter

Fluorescent tri-phosphor technology

Low light depreciation over lamp life

Applications

Designed for general or supplementary lighting in professional or home environments

Recessed or surface-mounted downlighters, wall units, table lamps and pendant lamps



