

MASTER PL-R Eco 14W/840/4P 1CT/5X10BOX

Kod produktu: 57701



Dane techniczne:

- Cap-Base **GR14q-1**
- Color Code **840 [CCT of 4000K]**
- Color Designation (text) **Cool White**
- Color Temperature **4000 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **17 kWh**
- Diameter D **41.0 (max) mm**
- Overall Length C **126.6 (max) mm**
- Full product code **927909984050**
- Full product name **MASTER PL-R Eco 14W/840/4P 1CT**
- Order code **927909984050**
- Order product name **MASTER PL-R Eco 14W/840/4P 1CT/5X10BOX**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500266002**
- Bar code on pack - EAN1 **8711500265982**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927909984050**
- Net weight per piece **70.000 gr**
- Bar code on intermediate packing - EAN2 **8711500265999**
- Cap-Base Information **4P**
- Lamp Wattage **14 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSM6H-14/40/1B-L/P-GR14q=1**
- Mercury (Hg) Content **1.4 mg**
- Insertion Length B **120.0 (max) mm**
- Chromaticity Coordinate X **387 -**
- Chromaticity Coordinate Y **389 -**
- Design Temperature **35 C**
- Base Face to Base Face A **99.7 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **99 %**
- LSF HF Preheat 12000h Rated,3h **97 %**
- LSF HF Preheat 6000h Rated,3h **99 %**

- LSF HF Preheat 8000h Rated,3h **98 %**
- LSF HF Preheat 16000h Rated,3h **94 %**
- LLMF HF 2000h Rated **96 %**
- LLMF HF 4000h Rated **94 %**
- LLMF HF 12000h Rated **91 %**
- LLMF HF 6000h Rated **93 %**
- LLMF HF 8000h Rated **92 %**
- Lum Efficacy Rated HF 25°C **72 Lm/W**
- LSF HF Preheat 20000h Rated,3h **87 %**
- LLMF HF 16000h Rated **90 %**
- LLMF HF 20000h Rated **89 %**
- Lum Flux Nom. HF 25°C,base up **1050 Lm**
- Luminous Flux EL 35°C base up **1200 Lm**
- Lum Flux Rated HF 25°C,base up **1050 Lm**
- Lamp Voltage EL 25°C base up **100 V**
- Lamp Wattage EL 35°C base up **15 W**
- Wattage EL 25°C base up, Nom. **14 W**
- Wattage EL 25°C base up, Rated **14.5 W**
- Lamp Current EL 25°C base up **0.150 A**

MASTER PL-R Eco is an extremely efficient compact fluorescent lamp for downlight applications. It consists of six parallel tubes with a new innovative 'twist and lock' lamp base, designed for operation with electronic gear. The MASTER PL-R Eco contains the original bridge technology invented and patented by Philips. This guarantees optimum performance in the application and results in significantly higher efficacies than with regular compact fluorescent lamps. On top of that, MASTER PL-R Eco lamps offer more than double the service life of a standard compact fluorescent lamp, thanks to superior lumen maintenance. The 'twist and lock' lamp base provides easy and safe (dis-)mounting and sturdy fixation in the luminaire.



