

PL-Q 16W/827/4P 1CT/10BOX

Kod produktu: 57705



Dane techniczne:

- Cap-Base **GR10q**
- Color Code **827 [CCT of 2700K]**
- Color Designation (text) **Incandescent White**
- Color Temperature **2700 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **18 kWh**
- Diameter D **15 (max) mm**
- Overall Length C **141 (max) mm**
- Full product code **927939182740**
- Full product name **PL-Q 16W/827/4P 1CT**
- Order code **927939182740**
- Order product name **PL-Q 16W/827/4P 1CT/10**
- Packing configuration **10**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500270023**
- Bar code on pack - EAN1 **8711500269881**
- Packs per outerbox **10**
- Logistic code(s) - 12NC **927939182740**
- Net weight per piece **68.000 gr**
- Cap-Base Information **4P**
- Lamp Wattage **16 W**
- Overall Width E **138 (max) mm**
- Color Rendering Index **82 Ra8**
- Overall Length Rim C1 **51 (max) mm**
- ILCOS code **FSS-16/27/1B-E-GR10q**
- Mercury (Hg) Content **4 mg**
- Chromaticity Coordinate X **463 -**
- Chromaticity Coordinate Y **420 -**
- Width F **41 (max) mm**
- Design Temperature **25 C**
- Lamp Wattage EM 25°C, Nominal **16 W**
- Lamp Current EM 25°C **0.195 A**
- Lamp Voltage EM 25°C **103 V**
- Lamp Wattage EM 25°C, Rated **16.0 W**

- Diameter D1 **27.5 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **60 %**
- LSF HF Preheat 6000h Rated,3h **95 %**
- LSF HF Preheat 8000h Rated,3h **89 %**
- LSF HF Preheat 16000h Rated,3h **22 %**
- LLMF HF 2000h Rated **91 %**
- LLMF HF 4000h Rated **86 %**
- LLMF HF 12000h Rated **79 %**
- LLMF HF 6000h Rated **83 %**
- LLMF HF 8000h Rated **81 %**
- Lamp Wattage EL 25°C, Rated **16.0 W**
- Lamp Voltage EL 25°C **93 V**
- Lamp Wattage EL 25°C, Nominal **16 W**
- Lamp Current EL 25°C **0.180 A**
- LSF HF Preheat 20000h Rated,3h **4 %**
- LLMF HF 16000h Rated **78 %**
- LLMF HF 20000h Rated **78 %**
- Cap Length U **40 (max) mm**
- Lum Flux Rated HF 25°C,horiz **1050 Lm**
- Lum Efficacy Rated HF 25°C,hor **66 Lm/W**
- Lum Flux Nominal HF 25°C,horiz **1050 Lm**

PL-Q is an efficient, square-shaped compact fluorescent lamp, typically used in decorative-lighting luminaires. While offering the advantage of energy-efficient operation, it also provides design freedom for flat ceiling or wall fixtures in particular, due to its low built-in height and uniform spread of light. The 4-pin version is designed for operation on electronic gear.

PL-Q is an efficient, square-shaped compact fluorescent lamp, typically used in decorative-lighting luminaires. While offering the advantage of energy-efficient operation, it also provides design freedom for flat ceiling or wall fixtures in particular, due to its low built-in height and uniform spread of light. The 4-pin version is designed for operation on electronic gear.

Features

4-pin base

Fluorescent tri-phosphor technology

Applications

Ideal for applications such as corridors, toilets, stairwells and reception areas



