

# PL-Q 16W/830/2P 1CT/10BOX

Kod produktu: 57706



## Dane techniczne:

- Cap-Base **GR8**
- Color Code **830 [CCT of 3000K]**
- Color Designation (text) **Warm White**
- Color Temperature **3000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **20 kWh**
- Diameter D **15 (max) mm**
- Overall Length C **141 (max) mm**
- Full product code **927939083040**
- Full product name **PL-Q 16W/830/2P 1CT**
- Order code **927939083040**
- Order product name **PL-Q 16W/830/2P 1CT/10**
- Packing configuration **10**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500270016**
- Bar code on pack - EAN1 **8711500269874**
- Packs per outerbox **10**
- Logistic code(s) - 12NC **927939083040**
- Net weight per piece **68.000 gr**
- Cap-Base Information **2P**
- Lamp Wattage **16 W**
- Overall Width E **138 (max) mm**
- Color Rendering Index **82 Ra8**
- Overall Length Rim C1 **51 (max) mm**
- ILCOS code **FSS-16/30/1B-I-GR8**
- Mercury (Hg) Content **4.0 mg**
- Chromaticity Coordinate X **440 -**
- Chromaticity Coordinate Y **403 -**
- Width F **41 (max) mm**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **96 %**
- LSF EM 6000h Rated,3h cycle **89 %**
- LSF EM 8000h Rated,3h cycle **73 %**
- LLMF EM 2000h Rated **91 %**

- Lum Efficacy Rated EM 25°C **66 Lm/W**
- Luminous Flux EM 25°C, Nominal **1050 Lm**
- Luminous Flux EM 25°C, Rated **1050 Lm**
- LLMF EM 4000h Rated **85 %**
- LLMF EM 6000h Rated **82 %**
- LLMF EM 8000h Rated **80 %**
- Design Temperature **25 C**
- Lamp Wattage EM 25°C, Nominal **16 W**
- Lamp Current EM 25°C **0.195 A**
- Lamp Voltage EM 25°C **103 V**
- Lamp Wattage EM 25°C, Rated **16.0 W**
- Diameter D1 **27.5 (max) mm**
- LLMF EM 12000h Rated **79 %**
- LLMF EM 16000h Rated **78 %**
- LLMF EM 20000h Rated **77 %**
- Lum Efficacy Rated EM 25°C,hor **66 Lm/W**
- Lum Flux Nominal EM 25°C,horiz **1050 Lm**
- Lum Flux Rated EM 25°C,horiz **1050 Lm**
- Cap Length U **40 (max) mm**

PL-Q is an efficient, square-shaped compact fluorescent lamp, typically used in decorative-lighting luminaires. While offering the advantage of energy-efficient operation, it also provides design freedom for flat ceiling or wall fixtures in particular, due to its low built-in height and uniform spread of light. The 2-pin version is designed for operation on electromagnetic gear.

PL-Q is an efficient, square-shaped compact fluorescent lamp, typically used in decorative-lighting luminaires. While offering the advantage of energy-efficient operation, it also provides design freedom for flat ceiling or wall fixtures in particular, due to its low built-in height and uniform spread of light. The 2-pin version is designed for operation on electromagnetic gear.

## Features

2-pin base with a housing incorporating the special instant starter and capacitor  
Fluorescent tri-phosphor technology

## Applications

Ideal for applications such as corridors, toilets, stairwells and reception areas



