

# PL-Q 28W/835/4P 1CT/10BOX

Kod produktu: 57714



## Dane techniczne:

- Cap-Base **GR10q**
- Color Code **835 [CCT of 3500K]**
- Color Designation (text) **White**
- Color Temperature **3500 K**
- Dimmable **Yes**
- Energy Efficiency Label (EEL) **A**
- Energy consumption kWh/1000h **31 kWh**
- Diameter D **24 (max) mm**
- Overall Length C **207 (max) mm**
- Full product code **927939383540**
- Full product name **PL-Q 28W/835/4P 1CT**
- Order code **927939383540**
- Order product name **PL-Q 28W/835/4P 1CT/10BOX**
- Packing configuration **10**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500269027**
- Bar code on pack - EAN1 **8711500269676**
- Packs per outerbox **10**
- Logistic code(s) - 12NC **927939383540**
- Net weight per piece **127.000 gr**
- Cap-Base Information **4P**
- Lamp Wattage **28 W**
- Overall Width E **205 (max) mm**
- Color Rendering Index **82 Ra8**
- Overall Length Rim C1 **77 (max) mm**
- ILCOS code **FSS-28/35/1B-E-GR10q**
- Mercury (Hg) Content **4 mg**
- Chromaticity Coordinate X **409 -**
- Chromaticity Coordinate Y **394 -**
- Width F **41 (max) mm**
- Design Temperature **25 C**
- Lamp Wattage EM 25°C, Nominal **28 W**
- Lamp Current EM 25°C **0.320 A**
- Lamp Voltage EM 25°C **108 V**
- Lamp Wattage EM 25°C, Rated **24.8 W**

- Diameter D1 **33 (max) mm**
- LSF HF Preheat 2000h Rated,3h **99 %**
- LSF HF Preheat 4000h Rated,3h **98 %**
- LSF HF Preheat 12000h Rated,3h **60 %**
- LSF HF Preheat 6000h Rated,3h **95 %**
- LSF HF Preheat 8000h Rated,3h **89 %**
- LSF HF Preheat 16000h Rated,3h **22 %**
- LLMF HF 2000h Rated **91 %**
- LLMF HF 4000h Rated **86 %**
- LLMF HF 12000h Rated **79 %**
- LLMF HF 6000h Rated **83 %**
- LLMF HF 8000h Rated **81 %**
- Lamp Wattage EL 25°C, Rated **24.8 W**
- Lamp Voltage EL 25°C **98 V**
- Lamp Wattage EL 25°C, Nominal **28 W**
- Lamp Current EL 25°C **0.255 A**
- LSF HF Preheat 20000h Rated,3h **4 %**
- LLMF HF 16000h Rated **78 %**
- LLMF HF 20000h Rated **78 %**
- Cap Length U **49 (max) mm**
- Lum Flux Rated HF 25°C,horiz **2050 Lm**
- Lum Efficacy Rated HF 25°C,hor **83 Lm/W**
- Lum Flux Nominal HF 25°C,horiz **2050 Lm**

PL-Q is an efficient, square-shaped compact fluorescent lamp, typically used in decorative-lighting luminaires. While offering the advantage of energy-efficient operation, it also provides design freedom for flat ceiling or wall fixtures in particular, due to its low built-in height and uniform spread of light. The 4-pin version is designed for operation on electronic gear.



