

MASTER PL-C Xtra 26W/840/2P 1CT/5X10BOX

Kod produktu: 57734



Dane techniczne:

- Cap-Base **G24d-3**
- Color Code **840 [CCT of 4000K]**
- Color Designation (text) **Cool White**
- Color Temperature **4000 K**
- Dimmable **No**
- Energy Efficiency Label (EEL) **B**
- Energy consumption kWh/1000h **32 kWh**
- Diameter D **27.1 (max) mm**
- Overall Length C **171.4 (max) mm**
- Full product code **927906284014**
- Full product name **MASTER PL-C Xtra 26W/840/2P 1CT**
- Order code **927906284014**
- Order product name **MASTER PL-C Xtra 26W/840/2P 1CT/5X10BOX**
- Packing configuration **5X10CC**
- Pieces per pack **1**
- Bar code on outerbox - EAN3 **8711500898883**
- Bar code on pack - EAN1 **8711500898869**
- Packs per outerbox **50**
- Logistic code(s) - 12NC **927906284014**
- Net weight per piece **64.300 gr**
- Bar code on intermediate packing - EAN2 **8711500898876**
- Cap-Base Information **2P**
- Lamp Wattage **26 W**
- Color Rendering Index **82 Ra8**
- ILCOS code **FSQ-26/40/1B-I-G24d=3**
- Mercury (Hg) Content **3.0 mg**
- Insertion Length B **149.0 (max) mm**
- Chromaticity Coordinate X **380 -**
- Chromaticity Coordinate Y **380 -**
- LSF EM 2000h Rated,3h cycle **99 %**
- LSF EM 4000h Rated,3h cycle **98 %**
- LSF EM 6000h Rated,3h cycle **97 %**
- LSF EM 8000h Rated,3h cycle **95 %**
- LLMF EM 2000h Rated **92 %**
- Lum Efficacy Rated EM 25°C **68 Lm/W**

- Luminous Flux EM 25°C, Nominal **1800 Lm**
- Luminous Flux EM 25°C, Rated **1800 Lm**
- LLMF EM 4000h Rated **87 %**
- LLMF EM 6000h Rated **84 %**
- LLMF EM 8000h Rated **81 %**
- Design Temperature **28 C**
- Lamp Wattage EM 25°C, Nominal **26 W**
- Lamp Current EM 25°C **0.325 A**
- Lamp Voltage EM 25°C **105 V**
- Lamp Wattage EM 25°C, Rated **26.5 W**
- Base Face to Base Face A **130.7 (max) mm**
- Diameter D1 **27.1 (max) mm**
- LSF EM 12000h Rated, 3h cycle **90 %**
- LSF EM 16000h Rated, 3h cycle **50 %**
- LLMF EM 12000h Rated **79 %**
- LLMF EM 16000h Rated **78 %**
- LLMF EM 20000h Rated **77 %**

This is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. MASTER PL-C Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-C lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

This is an efficient compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. MASTER PL-C Xtra lamps furthermore provide significantly lower operating costs thanks to their lifetime, which is more than double that of a standard MASTER PL-C lamp, and their very low early failure rate. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Features

2-pin base with a housing incorporating the special instant starter

Fluorescent tri-phosphor technology

Extra long lifetime and fewer early failures

Low light depreciation over lamp life

Applications

Designed for general or supplementary lighting in professional environments

Recessed or surface-mounted downlighters, wall units, table lamps and pendant lamps

Suitable for use in applications where maintenance costs are high (high ceilings, difficult to reach): department stores, supermarkets, warehouses, production halls and public areas

